

RC-2RP1N12RDEP - 1603370

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable connector, with Pg13.5 connection thread, straight, shielded: yes, Screw locking, M23, No. of pos.: 11+PE, type of contact: Pin, Solder connection, cable diameter range: 3 mm ... 10.5 mm

The figure shows the 12-pos. product version, with double bracket strain relief



Key Commercial Data

| | |
|--------------|---------------|
| Packing unit | 20 pc |
| GTIN | |
| GTIN | 4046356245135 |

Technical data

Data of the insulating body

| | |
|---|----------------------|
| Coding | N |
| Contact connection method | Solder connection |
| Type of contacts | Pin |
| Application | Signal |
| Number of positions | 12 |
| Contact diameter of power contacts | 1 mm |
| Litz wire cross section of power contacts min. | 0.08 mm ² |
| Litz wire cross section of power contacts max. | 1 mm ² |
| Nominal current per power contact at 25°C | 10 A |
| Nominal voltage, power contact | 150 V |
| Rated surge voltage | 1.5 kV |
| Overvoltage category | II |
| Degree of pollution | 3 |
| Contact diameter of signal contacts | 1 mm |
| Litz wire cross section of signal contacts min. | 0.08 mm ² |

RC-2RP1N12RDEP - 1603370

Technical data

Data of the insulating body

| | |
|---|-------------------|
| Litz wire cross section of signal contacts max. | 1 mm ² |
| Nominal current per signal contact at 25°C | 8 A |
| Nominal voltage, signal contact | 150 V |
| Overvoltage category | II |
| Degree of pollution | 3 |

Housing data

| | |
|--|---|
| Note | Order information: Order contact inserts and cable clamping/shield accessories separately |
| Housing material | Metal |
| Type of locking | Screw locking |
| Degree of protection (when plugged in) | IP67 |
| Thread type | M23 |

Cable seal data

| | |
|------------------|------------------|
| Cable diameter | 3 mm ... 10.5 mm |
| Sealing material | NBR |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|---------|
| EAC |  | B.01742 |
|-----|---|---------|

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>