




REV.	ECN NO.	DATE	SIGN	DESCRIPTION




⑦ Sealing Nut




⑥ Clamp Ring




⑤ Seals B2



④ Seals B1



③ Lock Nut







② Connector



① O-Ring

With Liquid Glue
點 防水 膠



Pin Assignments
Front View 前視圖

Note:

- * Seals B1 for Cable OD: $\varnothing 4.5\text{mm} \sim \varnothing 6.5\text{mm}$
(防水墊圈B1線徑: $\varnothing 4.5\text{mm} \sim \varnothing 6.5\text{mm}$)
- * Seals B2 for Cable OD: $\varnothing 3.5\text{mm} \sim \varnothing 5.3\text{mm}$
(防水墊圈B2線徑: $\varnothing 3.5\text{mm} \sim \varnothing 5.3\text{mm}$)
- * One Set Unassembled in One PE Bag
(每一組未組裝, 放置於一個PE袋, 並封口)
- * Important Dimension.
- * Waterproof Rate : IP66
- * Ring: Black, EPDM
- * Housing: Black, Nylon+GF
- * Pin: Copper Alloy, Gold Plated
- * Lock Nut: Black, Nylon+GF
- * Seals: Black, EPDM
- * Clamping Ring: Black, Nylon
- * Sealing Nut: Black, Nylon
- * PE Bag: 90mm*85mm
- * Liquid Glue: Clear

UNIT: mm		TITLE Standard, Assy Lock 3Pin F Conn M Pin	
TOLERANCE		SCALE 1:1	SIZE A4
.X ±0.25		REV. A	SHEET 1 OF 1
.XX ±0.1		WC-REV. A.3	QC: Inspection item
.XXX ±0.05			
ANGLES ±1°			

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO. BB-03BFMA-LL6001	DRAWN BY SamChang	DATE 2012-03-14
DWG NO. BB-03BFMA-LL6001	CHECKED BY Jeffrey	DATE 2012-03-20
CUSTOMER ALTW	APPROVED BY Kevin	DATE 2012-03-20