



SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

NOTES

MASS ± 5%	20.5 g
-----------	--------

MATERIALS	BLACK POLYAMID
BACKSHELL BODY	BLACK POLYAMID + CR
CABLE GLAND	

PERFORMANCES CHARACTERISTICS	
MECHANICAL	
TEMPERATURE CLASS	IEC61984/UL1977 -40°C TO 105°C
SEALING IN ASSEMBLY CONDITIONS	IEC60529 IP68 1BAR DURING 1WEEK
	DIN40050 IP69K
CORROSION SALT SPRAY	MIN 1000H

ROHS COMPLIANT

1. COUNTERPART REFERENCE UTL THREADED PLUG OR THREADED RECEPTACLE
2. CONNECTORS ARE DELIVERED AS PRE-ASSEMBLED KIT
3. CAPACITY C : Ø6.5 / Ø12
4. (*): OPTIONAL ORDERING PART NUMBERS TO BE ORDERED SEPARATELY
5. UNIT IN MM

Country	Jurisdiction & Control List
FR	NOT LISTED

P/N : UTL10JC

A	13/2/18	Creation	
ISS	DATE	Latest modification - by: --	MOD N°
Designed by: R.M.		Date: 13/2/18	CUSTOMER DRAWING
TITLE		THREADED BACKSHELL ASSEMBLY SIZE 10 UTL CONNECTOR	
Scale 1/1		General Linear Tolerances: ± 0.2	NPRDS / PROJECT BE170912A
SOURIAU		WWW.SOURIAU.COM	This document is the property of SOURIAU It must not be reproduced or communicated without permission
FORMAT A3	SOURIAU DRG N° UTL1-0107A-C		SHEET 1 / 1