





REV.	DATE	ECR NO.	DESCRIPTION
A	04/20/08	100005	UPDATE DRAWING FORMAT



RECOMMENDED
CABLE STRIPPING DIM'S



8					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007” .315 – 1.180 = ± 0.015” 1.180 – 4.724 = ± 0.020” DO NOT SCALE DRAWING	APPROVALS		DATE		Amphenol Connex N CRIMP REVERSE POLARIZED PLUG (FOR RG-223/U, 400/U)					
7						DRAWN	GRS	04/20/08							
6						CHECKED									
5						ISSUED				PART DESCRIPTION					
4	FERRULE	COPPER	NEXCOTE	1		SHEET	1 OF 1								
3	CONTACT PIN	PHOS. BRONZE	GOLD	1	CAD FILE C:/172/172142RP.DWG					PART NO. 172142RP					
2	INSULATOR	PTFE	NATURAL	1											
1	BODY	BRASS	NEXCOTE	1	DWG. NO. 172142RP.DWG					REV.	A	SIZE	A	SCALE	NA
	DESCRIPTION	MATERIAL	FINISH	QTY											