

## 1 Pt100 K 2515

The K Series Ceramic Wire Wound PRTDs are suitable for resistance thermometers requiring extremely temperature stability over 800°C and high temperature shock resistance.

Applications: Chemical and power generation plants, analytical equipment and for applications requiring extremely high temperature stability as well as high temperature shock resistance.

Construction: A platinum coil is sealed inside a high purity aluminum oxide ceramic body. Lead wires are shear force resistant and assure proper connection to extension leads and cables.



### Models

Description	Tolerance IEC 60751	Order No.	Dimensions mm				Self Heating 0°C (K/mW)	Response time			
			L	D	d	l		Water current V=0.4m/s		Air stream V=3m/s	
							t <sub>0.5</sub>	t <sub>0.9</sub>	t <sub>0.5</sub>	t <sub>0.9</sub>	
1Pt100 K 2515	W0.3	32.206.105	25 <sup>+2</sup> <sub>0</sub>	1.5±0.15	0.20±0.01	10.0±0.5	0.08	0.2	0.4	5.7	17.0
	W0.15	32.206.109									
	W0.1	32.206.152									

### Technical Specification

**Nominal resistance:** 100 Ohm @ 0 °C

**Temperature range:** W0.3 (Class B) = -196 to +850 °C  
(Heraeus exceeds IEC 60751: -196 to +660 °C)

W0.15 (Class A) = -196 to +600 °C  
(Heraeus exceeds IEC 60751: -100 to +450 °C)

W0.1 (Class 1/3 B) = -100 to +350 °C

**Temperature coefficient:** T<sub>c</sub> = 3850 ppm/K

**Leads:** Platinum-gold alloy

**Insulation resistance after assembly:** > 100 MOhm @ 25 °C

The measuring point is located at 8 mm from the end of the sensor body

**Measuring current:** 1 mA

**Tolerance class:** - According to IEC 60751:2008  
- Other standards and narrower tolerances are available on request

**Temperature stability:** Excellent long-term stability

**Also available:** - Different temperature coefficients (3916 ppm/K - old JIS)  
- Extension leads  
- Two separated coils can be embedded in one ceramic body

## Heraeus Sensor Technology USA

770 Township Line Road, Suite 300

Yardley, PA 19067 USA

Phone 1-215-944-9010 Fax 1-215-944-9392

Email [info.hst-us@heraeus.com](mailto:info.hst-us@heraeus.com)

[www.hst-us.com](http://www.hst-us.com)