

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

TWIST TIE

WITH PLUG CAPS

PANDUIT PART NUMBER	MIN. CABLE LENGTH	WEIGHT
IUTPCH3BLY	3 FT.	1.97 lbs/10 PCS (735.3 g/10 PCS)
IUTPCH5BLY	5 FT.	2.53 lbs/10 PCS (944.3 g/10 PCS)
IUTPCH7BLY	7 FT.	3.09 lbs/10 PCS (1153.3 g/10 PCS)
IUTPCH10BLY	10 FT.	3.93 lbs/10 PCS (1784.2 g/10 PCS)
IUTPCH15BLY	15 FT.	5.31 lbs/10 PCS (1981.9 g/10 PCS)
IUTPCH20BLY	20 FT.	6.70 lbs/10 PCS (2500.7 g/10 PCS)

NOTES:

- **1. SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS AND TO INDICATE COLOR AND OR PACKAGE QUANTITY.
2. SEE CATALOG FOR A COMPLETE LIST OF PARTS APPLICABLE FOR USE WITH THIS PART.
3. DIMENSIONS IN [] ARE IN METRIC.
4. NUT ON STRAIN RELIEF TAIL MUST BE TORQUED TO 20 IN-LBS TO MAINTAIN IP67 RATING
5. CABLE MEETS CATEGORY 5E REQUIREMENTS AND CURRENT ODVA REQUIREMENTS FOR INDUSTRIAL CABLE.

WITHOUT PLUG CAPS

PANDUIT PART NUMBER	MIN. CABLE LENGTH	WEIGHT
IUTPCHNC3BLY	3 FT.	1.53 lbs/10 PCS (692.84 g/10 PCS)
IUTPCHNC5BLY	5 FT.	1.99 lbs/10 PCS (901.84 g/10 PCS)
IUTPCHNC7BLY	7 FT.	2.45 lbs/10 PCS (1110.84 g/10 PCS)
IUTPCHNC10BLY	10 FT.	3.84 lbs/10 PCS (1741.74 g/10 PCS)
IUTPCHNC15BLY	15 FT.	4.28 lbs/10 PCS (1939.41 g/10 PCS)
IUTPCHNC20BLY	20 FT.	5.42 lbs/10 PCS (2458.24 g/10 PCS)

T568A WIRING

PLUG POSITION

1
2
3
4
5
6
7
8

CABLE WIRE
WHITE GREEN
GREEN
WHITE ORANGE
BLUE
WHITE BLUE
ORANGE
WHITE BROWN
BROWN

PLUG CAPS - ON IUTPCH*BLY PARTS ONLY

PART NUMBER		IUTPCH*BLY, IUTPCHNC*BLY	
TITLE		CATEGORY 5E INDUSTRIALNET, UTP, SOLID, PATCH CORD WITH PANDUIT PLUGS	
CUSTOMER DRAWING			
ITEM REVISION NAME		M02479LX/00	
DATASET FILE NAME		M02479LX_DC311/00B	
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]		MATERIAL:	
.x ± .xxx ± .010 [.3] .xx ± .03 [.8]		DRAWING NUMBER: 02479-311	
THIRD ANGLE PROJECTION		SHT 1 OF 1	
DRAWN BY	DATE	CHK	SCALE
LZ	3-18-06	WJC	NONE
DESCRIPTION		SIZE	
A. REVISED DRAWING TITLE BLOCK.		A	