




REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A5	REVISED (ECR-18-001061)	30JAN2018	E.Z	W.K.H



VIEW SHOWN WITH
MYLAR TAPE



SECTION Z-Z
SCALE 8:1







1 MATERIAL:
HOUSING: HIGH TEMP THERMOPLASTIC, UL94V-0, COLOR: BLACK
CONTACT: COPPER ALLOY
SOLDER PEG: COPPER ALLOY

2 FINISH:
CONTACT MATING AREA: GOLD PLATING OR GOLD FLASH OVER
PALLADIUM-NICKEL (SEE TABLE FOR
THICKNESS)
CONTACT SOLDER TAIL: MIN 2.54um MATTE TIN PLATING
SOLDER PEG: MIN 2.54um MATTE TIN PLATING
UNDERPLATE: MIN 1.27um NICKEL PLATING ALL OVER

3. PACKAGING: TAPE & REEL.
QTY: 500PCS/REEL

	0.76μm MIN	1735539-3
	0.38μm MIN	1735539-2
OBSOLETE	GOLD FLASH ONLY	1735539-1
	AU OR PD-NI THICKNESS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN SK LEAW 12MAR2008		 TE Connectivity	
		CHK SF LEONG 12MAR2008			
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME SLIMLINE SATA RECEPTACLE, VERTICAL, SMT, 6.5H	
mm		0 PLC ± 1 PLC ±0.4 2 PLC ±0.20 3 PLC ± 4 PLC ± ANGLES ±3°			
					
MATERIAL		FINISH			
				SIZE A2	
		WEIGHT -		CAGE CODE 00779	
		CUSTOMER DRAWING		DRAWING NO C=1735539	
				RESTRICTED TO -	
				SCALE 5:1	
				SHEET 1 of 2	
				REV A5	



RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE: ± 0.05