

Between Series Adaptor 33_716-QN-50-1/113_W

Description

PIM Adaptor plug/jack
7/16 plug (male) / QN jack (female)

Interface standards
Series 7/16 - IEC 61169-4_CECC 22190_DIN 47223_VG 95250
Series QN - QN QLF compliant



Benefits

Low passive intermodulation (PIM) adaptor
For Test & Measurement applications

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	7.5 GHz
PIM, 3rd order intermodulation distortion (IMD) max.	Static -155 dBc at 2x 43 dBm / 20 W carrier

Mechanical Data

Number of matings	100
Weight	0.0702 kg

Environmental Data

Operating temperature	-40 °C to 125 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Interface - 7/16 plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	EPDM (Ethylene propylene diene rubber)	

Interface - QN jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00013936
-----------------	--------------

Ordering Information

Single package	33_716-QN-50-1/113_WE
----------------	-----------------------

Remarks

3rd order passive intermodulation max.: static -165 dBc typ.

Between Series Adaptor 33_716-QN-50-1/113_W

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[33_716-QN-50-1/113_WE](#)