

Heavy-Duty Computer Power Cord, 15A, 14 AWG (IEC-320-C14 to IEC-320-C15), Green, 3 ft.

MODEL NUMBER: P018-003-AGN











Highlights

- Easy-to-identify green SJT jacket and fully molded green ends
- Flexible 14 AWG wire for easy routing
- 250V/15A rating
- UL-listed
- Recommended for Cisco®, HP and other C15-compatible hardware

Package Includes

 P018-003-AGN Heavy-Duty Computer Power Cord, Green, 3 ft.

Description

The P018-003-AGN Heavy-Duty Computer Power Cord features a green SJT jacket and fully molded green ends, allowing you to easily identify your connections in a crowded rack or workstation. It features a C14 male connector on one end and a C15 female connector on the other for attaching a high-voltage computer, server or storage drive to a PDU or UPS system.

This three-foot 15A cord supports voltages up to 250V. It's UL-listed and features a flexible SJT jacket and 14 AWG wire for easy routing through tight areas. The P018-003-AGN is recommended for Cisco, HP and other hardware that use C15 power connectors.

Features

Safe, Reliable Power Solution

- Connects PDU or UPS system with C14 input to network hardware with C15 power connectors
- Ideal for replacing an old or lost cord
- Recommended for Cisco, HP and other C15-compatible hardware

Color-Coded Cable and Connectors

• Colored green for easy identification in crowded rack or workstation

Optimum Construction

- 14 AWG wire
- Flexible SJT jacket
- 250V/15A rating
- UL-listed

Specifications





Cable Length (ft.) 3 Cable Length (m) 0.9 Cable Length (in.) 36 Cable Length (cm) 91.44 PHYSICAL Color Green ENVIRONMENTAL Operating Temperature Range -4 F to 221 F (-20 TO 105 C) Storage Temperature Range -4 F to 221 F (-20 TO 105 C) Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15 WARRANTY		
Cable Length (m) 0.9 Cable Length (in.) 36 Cable Length (cm) 91.44 PHYSICAL Color Green ENVIRONMENTAL Operating Temperature Range -4 F to 221 F (-20 TO 105 C) Storage Temperature Range -4 F to 221 F (-20 TO 105 C) Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15 WARRANTY IEC-320-C15	INPUT	
Cable Length (in.) 36 Cable Length (cm) 91.44 PHYSICAL Color Green ENVIRONMENTAL Operating Temperature Range -4 F to 221 F (-20 TO 105 C) Storage Temperature Range -4 F to 221 F (-20 TO 105 C) Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15	Cable Length (ft.)	3
PHYSICAL	Cable Length (m)	0.9
PHYSICAL Color Green ENVIRONMENTAL Operating Temperature Range -4 F to 221 F (-20 TO 105 C) Storage Temperature Range 10-85% RH Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15	Cable Length (in.)	36
Color Green ENVIRONMENTAL Operating Temperature Range -4 F to 221 F (-20 TO 105 C) Storage Temperature Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15	Cable Length (cm)	91.44
ENVIRONMENTAL Operating Temperature Range	PHYSICAL	
Operating Temperature Range -4 F to 221 F (-20 TO 105 C) Storage Temperature Range -4 F to 221 F (-20 TO 105 C) Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15	Color	Green
Storage Temperature Range -4 F to 221 F (-20 TO 105 C) Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15	ENVIRONMENTAL	
Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15	Operating Temperature Range	-4 F to 221 F (-20 TO 105 C)
Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15 WARRANTY	Storage Temperature Range	-4 F to 221 F (-20 TO 105 C)
CONNECTIONS Side A - Connector 1	Operating Humidity Range	10-85% RH
Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15 WARRANTY	Storage Humidity Range	10-85% RH
Side B - Connector 1 IEC-320-C15 WARRANTY	CONNECTIONS	
WARRANTY	Side A - Connector 1	IEC-320-C14
	Side B - Connector 1	IEC-320-C15
Product Warranty Period (Worldwide) Lifetime limited warranty	WARRANTY	
	Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies