






Load vacuum cover



	0.10
---	------




(All contacts and grounds)




Max. Temperature: 260° during 10 seconds.

0955 369 3811 741	1	M3	Black insulator	Reel Packaging: 140 connectors (See details on page2/2)
0955 369 3812 741	1	4-40 UNC		
0955 369 6811 741	2	M3		
0955 369 6812 741	2	4-40 UNC		
0955 369 7811 741	3	M3		
0955 369 7812 741	3	4-40 UNC		
Part number	PL	Nut	Index designation	

 All Dimensions in mm Original Size DIN A 3			Techn. Character.		Free size tolerances	
				Dat.	Name	D-Sub SMT, 25 poles Male, Straight with nuts and ground pins
			Detail.	25-Oct-11	Johnson.S	
			Insp.	17-Nov-11	Steven.W	
			Stand.	17-Nov-11	Steven.W	
			Scale 2 : 1			
EC04070	17-Nov-11	Johnson.S	Zhuhai HARTING Limited 			TB 09 55 369 x81x
Mod.	Dat.	Name				Sub. Page 1 / 2



Packaging in accordance with
EIA 481-2.



0955 369 3811 741	1	M3	Black insulator	Reel Packaging: 140 connectors
0955 369 3812 741	1	4-40 UNC		
0955 369 6811 741	2	M3		
0955 369 6812 741	2	4-40 UNC		
0955 369 7811 741	3	M3		
0955 369 7812 741	3	4-40 UNC		
Part number	PL	Nut	Index designation	

 All Dimensions in mm Original Size DIN A 3			Techn. Character.			Free size tolerances		
				Dat.	Name	Scale	D-Sub SMT, 25 poles Male, Straight with nuts and ground pins	
			Detail.	25-Oct-11	Johnson.S			
			Insp.	17-Nov-11	Steven.W			
			Stand.	17-Nov-11	Steven.W			
EC04070	17-Nov-11	Johnson.S	Zhuhai HARTING Limited 			TB	09 55 369 x81x	Page 2 / 2
Mod.	Dat.	Name				Sub.		