Shock-Safe Fuseholder, 5 x 20 mm, Fingergrip, horizontal or vertical



## 250 VAC/DC · 1.3 W / 10 A 10 A (UL/CSA)

See below:

**Approvals and Compliances** 

## **Description**

- Screw type fuse carrier
- PCB mounting horizontal or vertical

pdf data sheet, html datasheet, General Product Information, Packaging details, Distributor-Stock-Check, Detailed request for product, Microsite

Te			

Fuse-Link	5 x 20 mm
Mounting	PCB
Terminal	Solder THT
Rated Voltage	250 VAC/DC
Rated current	10A (UL/CSA)
Rated Power Acceptance IEC	1.3W / 10A @ Ta 23°C
Degree of Protection	IP 40
Protection Class	Suitable for appliances with protection
	class I or II acc. to IEC 61140
Admissible Ambient Air Temp.	-40 °C to 85 °C
Climatic Category	40/085/56 acc. to IEC 60068-1
Material: Socket	Thermoset, black
Material: Cap	Thermoplastic, black
Unit Weight	6 g
Storage Conditions	0°C to 60°C, max. 70% r.h.
Product Marking	5, Type, Rated Voltage, Rated current,
-	Certification marks

Soldering Methods	Wave		
	Soldering Profile		
Contact Resistance	$<$ m $\Omega$ at 100 mA		
Resistance to Vibration	acc. to NF C 20-706 / IEC 60068-2-6,		
	test Fc		
Shocks	acc. to NF C 20-706 / IEC 60068-2-27		
Bumps	acc. to NF C 20-729 / IEC 60068-2-29		

## **Approvals and Compliances**

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

## **Approvals**

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: 231409

Approval Logo	Certificates	Certification Body	Description	
<b>A</b> ®	UL Approvals	UL	UL File Number: E41738	
<b>®</b>	CSA Approvals	CSA	CSA Certification Record: LR 23151	
GAM T1				
NNO				

### **Product standards**

Product standards that are referenced

Organization	Design	Standard	Description
(UL)	Designed according to	UL 4248-1	Fuseholder general requirements



## **Application standards**

Application standards where the product can be used


Organization	Design	Standard	Description
<u>IEC</u>	Designed for applications acc.	IEC/UL 62368-1	IEC 62368-1 includes the basic requirements for safety of audio, video, information technology and office equipment.

## Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
C€		SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
<b>51)</b>	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

# **Dimension [mm]** 37.5 mm





a = 33.5 Variants 7091.4210, 7091.4240 and 7091.4270

a = 38.5 Variant 7091.4400

Drilling diagram

## **All Variants**

Holder	Сар	Mounting	Degree of Pro- tection	<b>W (</b>	GAM NNO	Reference	Order Number
•	Fingergrip	horizontal / vertical	IP40	• •	• •	231409	7091.4210
•	Fingergrip	vertical	IP40	•		231409L	7091.4240
•	Fingergrip	horizontal	IP40	•		231409F	7091.4270
•	Fingergrip	vertical	IP40			231632NL (*)	7091.4400

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

(\*) Not recommended for new designs

Packaging Unit Bulk (10 pcs.)