

Shock-Safe Fuseholder, 5 x 20 mm, Fingergrip, horizontal or vertical



250 VAC/DC · 1.3W/10A10A (UL/CSA)

See below:

[Approvals and Compliances](#)


### Description

- Screw type fuse carrier
- PCB mounting horizontal or vertical

### Weblinks

[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Packaging details](#), [Distributor-Stock-Check](#), [Detailed request for product](#), [Microsite](#)

### Technical Data

|                              |   |
|------------------------------|---|
| Fuse-Link                    | 5 x 20 mm   |
| Mounting                     | PCB   |
| Terminal                     | Solder THT  |
| Rated Voltage                | 250 VAC/DC  |
| Rated current                | 10 A (UL/CSA)   |
| Rated Power Acceptance IEC   | 1.3 W / 10 A @ Ta 23 °C   |
| Degree of Protection         | IP 40   |
| Protection Class             | Suitable for appliances with protection class I or II acc. to IEC 61140   |
| Admissible Ambient Air Temp. | -40 °C to 85 °C   |
| Climatic Category            | 40/085/56 acc. to IEC 60068-1   |
| Material: Socket             | Thermoset, black  |
| Material: Cap                | Thermoplastic, black  |
| Unit Weight                  | 6 g   |
| Storage Conditions           | 0 °C to 60 °C, max. 70% r.h.  |
| Product Marking              |  , Type, Rated Voltage, Rated current, Certification marks |

|                         |  |
|-------------------------|--|
| Soldering Methods       | Wave<br><a href="#">Soldering Profile</a>    |
| Contact Resistance      | < mΩ at 100 mA                               |
| Resistance to Vibration | acc. to NF C 20-706 / IEC 60068-2-6, test Fc |
| Shocks                  | acc. to NF C 20-706 / IEC 60068-2-27         |
| Bumps                   | acc. to NF C 20-729 / IEC 60068-2-29         |

### Approvals and Compliances



Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

### Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: 231409

| Approval Logo   | Certificates                  | Certification Body | Description                        |
|---|-------------------------------|--------------------|------------------------------------|
|  | <a href="#">UL Approvals</a>  | UL                 | UL File Number: E41738             |
|  | <a href="#">CSA Approvals</a> | CSA                | CSA Certification Record: LR 23151 |
| GAM<br>T1<br><b>NNO</b>   |                               |                    |                                    |

