Mallory Sonalert Products, Inc.					Part #: JT120-YG-CSL		
Sales Outline Drawing				Revision: C			
Na alfiantiana.							
pecifications:			T			I	
Stack Number:	1	2					
LED Color:	YELLOW	GREEN					
Connection Wires:	Yellow and Brown	Green and Brown					
LED Current Draw:	<230 mA	<190 mA					
Rated Voltage:			120 VAC				
Operating Voltage:		T	90-120 VAC				
Sound Level Category:	Loud	Loud	Loud	Loud		Loud	
Mode of Operation:	Continuous	Medium Pulse (5PPS)	Double Pulse (0.	Continuous for 5 sec then 0.1s be reset		•	
Connection:	Black and Gray Wires	Black and Gray Wires; Orange wire connected to	Black and Gray Wire wire connected to Grewire	oon/Vollow   black and G		Gray wires; Orange and Purp nected to Green/Yellow wire	
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max.		40mA Max.		
Loudness @ 1m:			80-85 dB(A) Ty	80-85 dB(A) Typ.			
Frequency:		2000 ± 500 Hz					
Total Max Current:		<460mA with all LED's and sound unit working					
Operating Temperature:	-25° ~ +60°C						
Lens Color:		Opaque White					
Material:	ABS FR15U						
Mounting Method:	Stainless Steel Pole						
Weight Typical (g):	690						
NEMA 12:	Approved						
Options:	Please contact factory.						
YELLOW							
GREEN		18.1 [459.8]————		GAS [ø5.2] aces	Ø0.57 [Ø]2  for wire		
2.4 [61.8]	1		#10 or 5mm screws for nounting 	4	2.04 [		
ED OPERATION: CONNECT	T STACK COLOR WIR	E TO DOWER AND RE	POWN WIRE TO POW	MOUNTII DIAGRAI			
LD OF LINATION.  CONNEC	I STACK COLOR WIR	L TO FOWER AND BE	COVIN WIRE TO POW	LIV.			
OUND OPERATION:	CONNECT GRAV AN	D BL ACK WIRES TO I	POWER FOR CONTIN	ווטוופ פטו	IND		
OUND OF LIVATION.			BLACK TO POWER A			CDEEN/VELLOW/WIDE	
	11-05 MEDIUM PULSE	CANNINE CHERRY &					