









P.C.B. HOLE DRILLINGS



FIXING-PLATE METAL BRACKET



Directive 2002/95/EC
RoHS
Compliant



NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN OVER 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. CONTACTS: COPPER ALLOY
PLATING: 8µin HARD GOLD OVER min. 50µin NICKEL
4. METAL BRACKET: ZINC DIE CAST; 300µin COPPER/40-120µin NICKEL/120-200µin TIN
5. THREADED INSERT: COPPER ALLOY; min. 200µin TIN OVER 80µin NICKEL
6. PCB-SNAP: COPPER ALLOY; min. 200µin TIN OVER 80µin NICKEL
PCB-HOLE: $\varnothing 3,1 \pm 0,1$; PCB THICKNESS 1.6mm
7. FIXING-PLATE: PBT GF UL 94 V-0, BLACK
8. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
9. CONNECTOR IS PART MARKED: 163A16359X CONEC ABC

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

				tolerance		 dim. in mm
				date	name	
				drawn	13.03.07	Lehmenkühler
				appd.	13.03.07	Mickenbecker
				norm	DIN 41652	
				d-old		
a	Origin					
rev.	description	date	name			

scale:	2:1 (5:1)		
material:	SEE NOTES		
title:	D-SUB MALE 90° 9pos. SOLDER PIN ANGLED 0.370inch thread insert,metal bracket,fixing-plate,snap		
dwg no:	Inventor	DIN-A3	
16K2A1804		sh: 1	
part no:	163A16359X		