


Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du propriétaire. Propriete de c FCI. Droits de reproduction FCI.



1. P/N: 10114548-XXXX LF

—LEAD FREE

— LENGTH CODE (UNIT : mm)
0150 — DIM. A: 150±10mm

- ① MMI PLUG: 20PIN PLUG WITH SHELL COVER
20PIN PLUG WITH SHELL COVER
- ② USB RECEPTACLE: A TYPE
- ③ USB CABLE:
28AWG*1P+24AWG*2C+BRAID, OD4.5MM, COLOR: WHITE.
- ④ CABLE TIE: COLOR WHITE.
- ⑤ INNERMOLD: LD-PE, COLOR WHITE.
- ⑥ OVERMOLD: 55P PVC, COLOR WHITE.
- ⑦ PCB: PADDLE CARD, MATERIAL FR4, 0.8mm THICKNESS.

3. PRODUCT SPEC:GS-12-653; PACKING SPEC: GS-14-1485


4. THE PRODUCT IS NOT INTENDED TO EXPOSED
TO A MANUFACTURING SOLDER PROCESS

5. ALL CABLE ASSEMBLIES SHALL BE TESTED 100%

FOR CONTINUITY AS DEFINED IN WIRING DIAGRAM
CONDUCTOR RESISTOR: ≤ 3.0 OHM; INSULATION RESISTOR: $\geq 10M$ OHM
HIPOT TESTING: 300V DC, 0.01S.

6. PRODUCT COMPLY WITH ROHS ENVIRONMENT STANDARD,
SIX HAZARD SUBSTANCES MUST BE CONTROLLED AS FOLLOW:
Cd<1000ppm; Pb Hg Cr6+ PBBB, PBDE<1000ppm.

WIRING DIAGRAM

[illegible]

PDM: Rev:A

3 STATUS: **Released**

Printed: Jun 16, 2010