

PANDUIT PART NUMBER	STUD SIZE	DIMENSIONS in.				
		A $\pm .03$	W $\pm .01$	C $\pm .02$	M $\pm .03$	H $\pm .01$
PNF 18-6FF-3K	#6	.80 (20.32)	.28 (7.11)	.19 (4.83)	.64 (16.26)	.15 (3.81)
PNF 18-8FF-3K	#8	.87 (22.10)	.31 (7.87)	.23 (5.84)	.68 (17.27)	.17 (4.32)
PNF 18-10FF-3K	#10	.86 (21.84)	.35 (8.89)	.23 (5.84)	.68 (17.27)	.20 (5.08)

1. UL LISTED AND CSA CERTIFIED FOR :
A. 600 V MAX. VOLTAGE RATING
B. 221°F (105°C) MAX. TEMP. RATING
C. #22-18 AWG (0.5-1.5 mm²) SOLID
OR STRANDED, COPPER WIRE

A. PRESSES - CP-851, CP-860, CP-861
B. APPLICATOR - CA-800
C. DIE INSERTS - CD-800-1


CONTINUOUS MOLDED CARRIER STRIP

A. STAMPING - .03"(.8) THK COPPER, TIN PLATED
B. HOUSING - RED NYLON
C. SLEEVE - BRASS, TIN PLATED

U_L

LISTED
587H
E52164

A diagram showing a three-toothed gear meshing with a rack. The gear is on the left, and the rack is on the right. The rack has a horizontal line representing its pitch circle, and the gear's teeth are shown meshing with it.



06	1/01	KMD		CAD FILE SPEC. WAS N41202AA_PCD_05			
05	12/98	JAMB		ADDED DIM., "MIN. WIRE INSUL DIA."	05403		
REV	DATE	BY	CHK	DESCRIPTION	ECN	CUST	PM

PANDUIT

TINLEY PARK, ILLINOIS

TERMO 3PC. CONTINUOUSLY MOLDED NYLON (FUNNEL)
INSULATED, 22-18 BARREL, FLANGED FORKS

FF

LA

NONE

A41202