



## Main

|                               |   |
|-------------------------------|---|
| Range of product              | OsiSense XX                                   |
| Sensor type                   | Ultrasonic sensor                             |
| Series name                   | General purpose                               |
| Sensor name                   | XXV   |
| Sensor design                 | Cylindrical M18                               |
| Detection system              | Diffuse                                       |
| [Sn] nominal sensing distance | 0.16 ft (0.05 m) fixed                        |
| Material                      | Metal   |
| Type of output signal         | Discrete                                      |
| Discrete output function      | 1 NC  |
| Wiring technique              | 3-wire  |
| Discrete output type          | PNP   |
| [Us] rated supply voltage     | 12...24 V DC with reverse polarity protection |
| Electrical connection         | Male connector M12 4 pins                     |
| [Sd] sensing range            | 0.01...0.16 ft (0.003...0.05 m)               |
| Beam angle                    | 10 °  |
| IP degree of protection       | IP67 conforming to IEC 60529                  |

## Complementary

|   |   |
|---|---|
| Enclosure material                                | Brass   |
| Front material                                    | Epoxy   |
| Thread type                                       | M18 x 1   |
| Supply voltage limits                             | 10...36 V DC                                      |
| [Sa] assured operating distance                   | 0.01...0.16 ft (0.003...0.05 m)                   |
| Maximum differential travel                       | 0.12 in (3 mm)                                    |
| Blind zone  | 0...0.12 in (0...3 mm)                            |
| Transmission frequency                            | 360 kHz   |
| Repeat accuracy                                   | 1.5 %   |
| Deviation angle from 90° of object to be detected | -8...8 °  |
| Minimum size of detected object                   | Cylinder diameter 2 mm at 0.02 m                  |
| Status LED  | 1 LED (yellow) output state                       |
| Current consumption                               | 15 mA   |
| Maximum switching current                         | 200 mA with overload and short-circuit protection |
| Voltage drop                                      | < 2 V   |
| Switching frequency                               | <= 80 Hz  |
| Delay first up                                    | 5 ms  |
| Delay response                                    | 4 ms  |
| Delay recovery                                    | 4 ms  |
| Marking   | CE  |
| Threaded length                                   | 2.01 in (51 mm)                                   |
| Height  | 0.71 in (18 mm)                                   |
| Width   | 0.71 in (18 mm)                                   |
| Depth   | 2.95 in (75 mm)                                   |
| Product weight                                    | 0.11 lb(US) (0.05 kg)                             |

## Environment

|           |               |
|-----------|---------------|
| standards | IEC 60947-5-2 |
|-----------|---------------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                                       |  |
|---------------------------------------|--|
| product certifications                | CULus  |
| ambient air temperature for operation | 32...140 °F (0...60 °C)                                |
| ambient air temperature for storage   | -40...176 °F (-40...80 °C)                             |
| vibration resistance                  | +/- 2 mm conforming to IEC 60068-2-6 10...55 Hz        |
| shock resistance                      | 50 gn in all 3 axes 11 ms conforming to IEC 60068-2-27 |
| resistance to electrostatic discharge | 8 kV level 4 conforming to IEC 61000-4-2               |
| resistance to electromagnetic fields  | 9.14 V/yd (10 V/m) level 3 conforming to IEC 61000-4-3 |
| resistance to fast transients         | 1 kV level 3 conforming to IEC 61000-4-4               |


Offer Sustainability

|  |  |
|--|--|
| Not Green Premium product  | Not Green Premium product  |
| Will not be Compliant  | Will not be Compliant  |
| WARNING: This product can expose you to chemicals including:   | WARNING: This product can expose you to chemicals including:   |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |


Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Dimensions



Minimum Mounting Distances



e(1) 25 mm

>

e(2) 700 mm

>


e(3) 60 mm

>

Wiring Diagram

3-Wire Type

NC outputs, PNP




(1) (+)

(3) (-)

## Curves


### Square Object



(3)

- (1) Parallel movement
- (2) Distance
- (3) Blind zone for diffuse sensors.

### Cylindrical Object



(3)

- (1) Parallel movement
- (2) Distance
- (3) Blind zone for diffuse sensors.