

8	FERRULE	BRASS	NEXCOTE	1	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020" DO NOT SCALE DRAWING	APPROVALS	DATE	Amphenol Connex					
7	CONTACT PIN	PHOSPHOR BRONZE	GOLD	1		DRAWN S.LI	05/25/12						
6	HEX NUT	BRASS	NEXCOTE	1		CHECKED		PART DESCRIPTION N BULKHEAD CRIMP JACK – LMR 200 (FOR RG–174/U,188A/U,316/U CABLE)					
5	LOCK WASHER	BRASS	NEXCOTE	1		ISSUED							
4	GASKET	SILICONE RUBBER	RED	1		SHEET 1 OF 1		PART NO. 172217					
3	BARREL	BRASS	NEXCOTE	1		CAD FILE C:/CONNEX/172217.DWG							
2	INSULATOR	PTFE	NATURAL	1				DWG. NO. 172217REV. ASIZE ASCALE NA					
1	BODY	BRASS	NEXCOTE	1									
	DESCRIPTION	MATERIAL	FINISH	QTY									