

## SENCITY® OMNI-S cellular + LTE stick antenna N-male 1399.17.0237

### Description

Omni - directional multiband antenna for GSM 1800, GSM/PCS 1900, UMTS, LTE 2300, 2500 and 2600,  
Also WLAN IEEE 802.11 b/g WiFi 2400 to 2500 MHz  
Gain 2 dBi, vertical polarized antenna  
Ingress protection IP67 (IEC 60529)  
For outdoor and indoor applications  
Pole or wall mount



### Product Configuration

### Technical Data

#### Electrical Data

	Band 1
Frequency (MHz)	1710 - 2690
VSWR	1.8
Impedance (Ohm)	50
Gain (dBi)	2
3dB beamwidth (h) (°)	360
3dB beamwidth (v) (°)	65
Composite power max (W)	25
Ambient temperature (°C)	25

#### Ports

	Port 1
Connector	N, plug (male)
Polarization	vertical
DC grounded	Yes

#### General Data

IMD level 145 dBc at carrier power 2x 30dBm

#### Mechanical Data

Dimensions (mm) 120 x 22 (Height x Diameter)  
Weight (kg) 0.3

#### Environmental Data

Environmental conditions outdoor  
Operation temperature (°C) -40 to 85  
Storage temperature (°C) -55 to 85  
Transport temperature (°C) -40 to 85  
IP rating IP67  
2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant  
Lead-free soldered yes  
WEEE 2012/19/EU special marking needed  
REACH 1907/2006/EC compliant

LOW TEMPERATURE: IEC 60068-2-1 72h -55°C  
HIGH TEMPERATURE: IEC 60068-2-2 72h +85°C  
HUMIDITY: ETSI EN300-2-4 T4, 1E 144h 95%  
SALT SPRAY: EN 60068-2-11 / GB-T 10125 96h

## SENCITY® OMNI-S cellular + LTE stick antenna N-male 1399.17.0237

MECHANICAL SHOCK: IEC 60721-3-4, 4M5

VIBRATION: IEC 60721-3-4 30 min/axis random 4M5

### Material Data

Radome colour	RAL 9003 (signal white)
Radome material	Glass Fibre

### Related Documents

Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00301627
3D-model	DOC-0000719263

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[1399.17.0237](#)