







- ① MATERIAL:
HOUSING: LCP, GLASS FILLED, UL94V-0.
TERMINALS: HIGH PERFORMANCE COPPER ALLOY.
- ② FINISH:
30μ" MIN GOLD IN CONTACT AREA. SELECTIVE TIN
ON PCB TAILS, NICKEL OVERALL.
- ③ FINISH:
30μ" MIN GOLD IN CONTACT AREA. SELECTIVE TIN-LEAD
ON PCB TAILS, NICKEL OVERALL.
4. SCREWS PACKAGED IN END OF PACKAGING TUBE.
- ⑤ FOR GROUNDED GUIDE PIN USE $\varnothing 3.56 \pm 0.08$ PTH,
 $\varnothing 3.66$ DRILL, AND $\varnothing 6.5$ PAD.
6. KEYING PIN SHOWN IN POSITION A, SEE KEYING CHART
ON SHEET 2 FOR OTHER POSITIONS.



LEFT GUDIED
BACKPLANE HOLE PATTERN
(CONNECTOR SIDE)

[illegible]

LOC	DIST	REVISIONS					
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-		SEE SHEET 1	-	-	-

	H	5.5	8-2007873-6
	H	4.9	8-2007873-5
	H	4.5	8-2007873-4
	H	5.5	8-2007873-3
	H	4.9	8-2007873-2
	H	4.5	8-2007873-1
	G	5.5	7-2007873-6
	G	4.9	7-2007873-5
	G	4.5	7-2007873-4
	G	5.5	7-2007873-3
	G	4.9	7-2007873-2
	G	4.5	7-2007873-1
	F	5.5	6-2007873-6
	F	4.9	6-2007873-5
	F	4.5	6-2007873-4
	F	5.5	6-2007873-3
	F	4.9	6-2007873-2
	F	4.5	6-2007873-1
	E	5.5	5-2007873-6
	E	4.9	5-2007873-5
	E	4.5	5-2007873-4
	E	5.5	5-2007873-3
	E	4.9	5-2007873-2
	E	4.5	5-2007873-1
	D	5.5	4-2007873-6
	D	4.9	4-2007873-5
	D	4.5	4-2007873-4
	D	5.5	4-2007873-3
	D	4.9	4-2007873-2
	D	4.5	4-2007873-1
	C	5.5	3-2007873-6
	C	4.9	3-2007873-5
	C	4.5	3-2007873-4
	C	5.5	3-2007873-3
	C	4.9	3-2007873-2
	C	4.5	3-2007873-1
	B	5.5	2-2007873-6
	B	4.9	2-2007873-5
	B	4.5	2-2007873-4
	B	5.5	2-2007873-3
	B	4.9	2-2007873-2
	B	4.5	2-2007873-1
	A	5.5	1-2007873-6
	A	4.9	1-2007873-5
	A	4.5	1-2007873-4
	A	5.5	1-2007873-3
	A	4.9	1-2007873-2
	A	4.5	1-2007873-1
	-	5.5	2007873-6
	-	4.9	2007873-5
	-	4.5	2007873-4
	-	5.5	2007873-3
	-	4.9	2007873-2
	-	4.5	2007873-1
FINISH	KEY POSITION	DIM M	PART NUMBER

REFER TO WWW.TE.COM
FOR PRODUCT AVAILABILITY

KEY POSITION
CHART

NONE

A

E

B

F

C

G

D

H