

Product data sheet

Characteristics

8501KFDR12V60

Plug in relay, flange mounted, DPDT, 10 amp
at 277 VAC, 110 VDC coil



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product range	8501K
Product type	Relay
Relay type	General purpose
Mounting type	Flange
Contact composition	DPDT
[Uc] control circuit voltage	110 V DC
Manual operator	Without test button

Complementary

Horsepower rating	1 hp 277 V AC
Maximum switching voltage	300 V AC 30 V DC
Contact material	Silver alloy (AgNi)
Operating time	20 ms - pick-up 20 ms - drop-out
Shape of pins	Spade

Environment

Ambient temperature range - operational	-40...55 °C (-40...131 °F)
Product certifications	UL recognized CSA CE RoHS
Height	69.85 mm (2.75 in)
Width	35.56 mm (1.4 in)
Depth	35.56 mm (1.4 in)

Ordering and shipping details

Category	21145 - 8501 KF, KL
Discount Schedule	CP2
GTIN	00785901995586
Package weight(Lbs)	0.09 kg (0.2 lb(US))
Returnability	No
Country of origin	CN

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes

Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations