


### Applications


- Electronic Warfare
- Commercial and Military Radar

### Product Features

- Frequency Range: 6 - 12 GHz
- Output Power: > 45 dBm ( $P_{IN} = 23$  dBm)
- PAE: > 25 % ( $P_{IN} = 23$  dBm)
- Large Signal Gain: > 22.0 dB
- $V_D = 20$  V,  $I_{DQ} = 2.0$  A,  $V_G = -2.4$  V typ.
- Chip Dimensions: 5.4 mm x 7.0 mm x 0.10 mm



### Functional Block Diagram



### General Description

TriQuint's TGA2590 is a wideband power amplifier fabricated on TriQuint's production 0.25um GaN on SiC process. The TGA2590 operates from 6 - 12GHz and provides greater than 30W of saturated output power with greater than 22 dB of large signal gain and greater than 25% power-added efficiency.

The TGA2590 is fully matched to 50Ω with DC blocking caps at both RF ports allowing for simple system integration. The broadband performance supports electronic warfare and radar across defense and commercial markets.

Lead-free and RoHS compliant.

Evaluation boards are available upon request.

*The information contained on this data sheet is technical information as defined by 22 CFR 120.10 and is therefore US export controlled. Export or transfer contrary to US law is prohibited.*

### Pad Configuration

Pad No.	Symbol
1	RF In
2, 14	$V_{G1}$
3, 13	$V_{G2}$
4, 12	$V_{D1}$
5, 11	$V_{D2}$
6, 10	$V_{G3}$
7, 9	$V_{D3}$
8	RF Out

### Ordering Information

Part	ECCN	Description
TGA2590	3A001.b.2.b	6-12 GHz 30W PA

### Absolute Maximum Ratings

Parameter	Value
Drain Voltage ( $V_D$ )	40 V
Gate Voltage Range ( $V_G$ )	-8 to 0 V
Drain Current w/ RF Drive ( $I_{D\_DRIVE}$ )	8.0
Gate Current ( $I_G$ )	-20 to 60 mA
Power Dissipation ( $P_{DISS}$ )	115 W
Input Power, CW, 50 $\Omega$ , 85 °C ( $P_{IN}$ )	30 dBm
Input Power, CW, 6:1 VSWR, 85 °C ( $P_{IN}$ )	27 dBm
Channel temperature ( $T_{CH}$ )	275 °C
Mounting Temperature (30 Seconds maximum)	320 °C
Storage Temperature	-55 to 150 °C

Operation of this device outside the parameter ranges given above may cause permanent damage. These are stress ratings only, and functional operation of the device at these conditions is not implied.

### Recommended Operating Conditions

Parameter	Value
Drain Voltage ( $V_D$ )	20 V
Drain Current ( $I_{DQ}$ )	2.0 A
Drain Current w/ RF Drive ( $I_{D\_DRIVE}$ )	< 7.0 A
Gate Voltage ( $V_G$ ), typ.	- 2.4 V
Input Power ( $P_{IN}$ )	+17 to +25 dBm
Load VSWR	< 2.0:1

Electrical specifications are measured at specified test conditions. Specifications are not guaranteed over all operating conditions.

### Electrical Specifications

Test conditions unless otherwise noted: 25 °C,  $V_D = 20$  V,  $I_{DQ} = 2.0$  A,  $V_G = -2.4$  V typ.

Parameter	Min	Typical	Max	Units
Operational Frequency Range	6.0		12.0	GHz
Output Power ( $P_{IN} = 23$ dBm)		46.0		dBm
Power Added Efficiency ( $P_{IN} = 23$ dBm)		32.5		%
Input Return Loss		13.0		dB
Output Return Loss		11.0		dB
Output Power Temperature Coefficient		-0.02		dBm/ °C
Input Power	17.0		25.0	dBm
Load VSWR			2.0:1	

The information contained on this data sheet is technical information as defined by 22 CFR 120.10 and is therefore US export controlled. Export or transfer contrary to US law is prohibited.

### Thermal and Reliability Information


Parameter	Test Conditions	Value	Units
Thermal Resistance ( $\theta_{JC}$ ) <sup>(1)</sup>	$T_{BASE} = 85^{\circ}C, V_D = 20V, I_{D\_Drive} = 5.5 A,$ $P_{IN} = 23 dBm, P_{OUT} = 44 dBm, P_{DISS} =$ $85 W$	1.3	$^{\circ}C/W$
Channel Temperature ( $T_{CH}$ )		201	$^{\circ}C$
Median Lifetime ( $T_M$ )		1.16E7	Hrs
Thermal Resistance ( $\theta_{JC}$ ) <sup>(1)</sup>	$T_{BASE} = 85^{\circ}C, V_D = 25V, I_{D\_Drive} = 5.8 A,$ $P_{IN} = 23 dBm, P_{OUT} = 45.6 dBm, P_{DISS} =$ $109 W$	1.4	$^{\circ}C/W$
Channel Temperature ( $T_{CH}$ )		237	$^{\circ}C$
Median Lifetime ( $T_M$ )		6.15E5	Hrs

Notes:

- MMIC soldered to 20 mil thick Cu-Mo carrier plate using 1.5 mil thick AuSn solder. Thermal resistance is determined from the channel to the back of the carrier plate (fixed 85  $^{\circ}C$  temp.).







### Median Lifetime

Test Conditions: 40 V; Failure Criteria = 10% reduction in  $I_{D\_MAX}$









The information contained on this data sheet is technical information as defined by 22 CFR 120.10 and is therefore US export controlled. Export or transfer contrary to US law is prohibited.

### Typical Performance







The information contained on this data sheet is technical information as defined by 22 CFR 120.10 and is therefore US export controlled. Export or transfer contrary to US law is prohibited.

### Typical Performance









The information contained on this data sheet is technical information as defined by 22 CFR 120.10 and is therefore US export controlled. Export or transfer contrary to US law is prohibited.

### Typical Performance




The information contained on this data sheet is technical information as defined by 22 CFR 120.10 and is therefore US export controlled. Export or transfer contrary to US law is prohibited.

**Typical Performance**



The information contained on this data sheet is technical information as defined by 22 CFR 120.10 and is therefore US export controlled. Export or transfer contrary to US law is prohibited.

**Application Circuit**



**Bias-up Procedure**

1. Set  $I_D$  limit to 8.0,  $I_G$  limit to 150mA
2. Set  $V_G$  to -5.0V
3. Set  $V_D$  +20V
4. Adjust  $V_G$  more positive until  $I_{DQ} = 2.0$  A
5. Apply RF signal


**Bias-down Procedure**

1. Turn off RF signal
2. Reduce  $V_G$  to -5.0V. Ensure  $I_{DQ} \sim 0$ mA
3. Set  $V_D$  to 0V
4. Turn off  $V_D$  supply
5. Turn off  $V_G$  supply

The information contained on this data sheet is technical information as defined by 22 CFR 120.10 and is therefore US export controlled. Export or transfer contrary to US law is prohibited.



### Evaluation Board




### Bill of Materials

Ref. Designation	Value	Description	Manufacturer	Part Number
C1 – C8	1000 pF	SLC, 50V	Various	
C9, C11, C13, C14	0.1 uF	Cap, 0402, 50V, 10%, X7R	Various	
C10, C12	10 uF	Cap, 1206, 50V, 10%, X7R	Various	
R1, R2, R5, R6	0 Ω	Res, 0402	Various	
R3 – R4	5.1 Ω	Res, 0402	Various	

The information contained on this data sheet is technical information as defined by 22 CFR 120.10 and is therefore US export controlled. Export or transfer contrary to US law is prohibited.

### Mechanical Drawing & Bond Pad Description



Unit: millimeters

Thickness: 0.10

Die x, y size tolerance: +/- 0.050

Chip edge to bond pad dimensions are shown to center of pad

Ground is backside of die

Bond Pad	Symbol	Description
1	RF In	Input; matched to 50 ohms; AC coupled.
2, 14	$V_{G1}$	Gate voltage, $V_{G1}$ top and bottom. $V_{G1}$ top (pad 2) internally connected to $V_{G2}$ top (pad 3); $V_{G1}$ bottom (pad 14) internally connected to $V_{G2}$ bottom (pad 13).
3, 13	$V_{G2}$	Gate voltage, $V_{G2}$ top and bottom. Bias network required; must be biased from both sides. $V_{G1}$ top (pad 2) internally connected to $V_{G2}$ top (pad 3); $V_{G1}$ bottom (pad 14) internally connected to $V_{G2}$ bottom (pad 13).
4, 12	$V_{D1}$	Drain voltage, $V_{D1}$ top and bottom. Bias network required; must be biased from both sides.
5, 11	$V_{D2}$	Drain voltage, $V_{D2}$ top and bottom. Bias network required; must be biased from both sides.
6, 10	$V_{G3}$	Gate voltage, $V_{G3}$ top and bottom. Bias network required; must be biased from both sides.
7, 9	$V_{D3}$	Drain voltage, $V_{D3}$ top and bottom. Bias network required; must be biased from both sides.
8	RF Out	Output; matched to 50 ohms; AC coupled.

The information contained on this data sheet is technical information as defined by 22 CFR 120.10 and is therefore US export controlled. Export or transfer contrary to US law is prohibited.

## Assembly Notes

Component placement and adhesive attachment assembly notes:

- Vacuum pencils and/or vacuum collets are the preferred method of pick up.
- Air bridges must be avoided during placement.
- The force impact is critical during auto placement.
- Organic attachment (i.e. epoxy) can be used in low-power applications.
- Curing should be done in a convection oven; proper exhaust is a safety concern.

Reflow process assembly notes:

- Use AuSn (80/20) solder and limit exposure to temperatures above 300°C to 3-4 minutes, maximum.
- An alloy station or conveyor furnace with reducing atmosphere should be used.
- Do not use any kind of flux.
- Coefficient of thermal expansion matching is critical for long-term reliability.
- Devices must be stored in a dry nitrogen atmosphere.

Interconnect process assembly notes:

- Thermosonic ball bonding is the preferred interconnect technique.
- Force, time, and ultrasonics are critical parameters.
- Aluminum wire should not be used.
- Devices with small pad sizes should be bonded with 0.0007-inch wire.

*The information contained on this data sheet is technical information as defined by 22 CFR 120.10 and is therefore US export controlled. Export or transfer contrary to US law is prohibited.*

## Product Compliance Information

### ESD Sensitivity Ratings



Caution! ESD-Sensitive Device

ESD Rating: TBD  
Value: TBD  
Test: Human Body Model (HBM)  
Standard: JEDEC Standard JESD22-A114

### ECCN

US Department of State: 3A001.b.2.b

### Solderability

Use only AuSn (80/20) solder and limit exposure to temperatures above 300 °C to 3-4 minutes, maximum.

### RoHS-Compliance

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C<sub>15</sub>H<sub>12</sub>Br<sub>4</sub>O<sub>2</sub>) Free
- PFOS Free
- SVHC Free

## Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about TriQuint:

**Web:** [www.triquint.com](http://www.triquint.com)

**Email:** [info-sales@triquint.com](mailto:info-sales@triquint.com)

**Tel:** +1.972.994.8465

**Fax:** +1.972.994.8504

For technical questions and application information:

**Email:** [info-products@triquint.com](mailto:info-products@triquint.com)

## Important Notice

The information contained herein is believed to be reliable. TriQuint makes no warranties regarding the information contained herein. TriQuint assumes no responsibility or liability whatsoever for any of the information contained herein. TriQuint assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for TriQuint products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

TriQuint products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

*The information contained on this data sheet is technical information as defined by 22 CFR 120.10 and is therefore US export controlled. Export or transfer contrary to US law is prohibited.*