




LOC	DIST	REVISIONS					
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			A	RELEASED FOR PRODUCTION	02MAR2016	TX	SH




- MATERIALS:
CAGE ASSEMBLY- NICKEL SILVER ALLOY PER ASTM B 122.
BRACKET- NICKEL SILVER ALLOY PER ASTM B 122.
EMI SPRING- COPPER ALLOY, NICKEL PLATED.
EMI GASKET- PLATED FILLED SILICONE.
HOUSING- POLYESTER LCP WITH 94 V-0
CHICKLET- POLYESTER LCP WITH 94 V-0
CONTACT- COPPER ALLOY.
LIGHTPIPE- POLYCARBONATE WITH 94 V-0
- CONTACT FINISH: 0.76µm GOLD ON MATING END, 1.25µm TIN ON SOLDER TAIL, ALL OVER 1.27µm NICKEL.
- DATUM AND BASIC DIMENSION ESTABLISHED BY CUSTOMER.
- MINIMUM PCB THICKNESS OF 1.57.
- THE ENTIRE AREA OF THE CONNECTOR FOOTPRINT, INDICATED BY THE DASHED LINE, TO BE CONSIDERED THE KEEPOUT AREA FOR COMPONENTS.
- CROSS-HATCHED AREAS REPRESENT ZONES ON THE PCB THAT COME IN CONTACT WITH OR BE IN CLOSE PROXIMITY TO THE PLASTIC HOUSING OR THE CONNECTOR CAGE. INDICATED AREAS TO BE CONSIDERED TRACE FREE.
- PART NUMBER AND DATE CODE MAKED IN APPROXIMATE AREA SHOWN.
- THESE HOLES ARE OPTIONAL WHEN PINS ON BACK OF CAGE ARE REMOVED.
- HATCHED AREA IS PLACEMENT ZONE FOR LED. LED SHOULD BE CENTERED WITHIN ZONE. RECOMMEND 0805 PACKAGE.
- CONTACT FINISH: 0.08µm MINIMUM GOLD OVER 0.68µm PALLADIUM-NICKEL ON MATING END, 1.25µm TIN ON SOLDER TAIL, ALL OVER 1.27µm NICKEL.


	LEFT INDICATOR DOWN	2227226-6
	LEFT INDICATOR UP	2227226-5
	NO LIGHTPIPE	2227226-4
	LEFT INDICATOR DOWN	2227226-3
	LEFT INDICATOR UP	2227226-2
	NO LIGHTPIPE	2227226-1
CONTACT FINISH	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER: ASME Y14.5M-2009		DWN: M. SHIRK 01AUG2012 CHK: D. SZCZESNY 01AUG2012 APVD: -	TE Connectivity	
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	PRODUCT SPEC: 108-60102 APPLICATION SPEC: 114-60015	NAME: CAGE AND CONNECTOR ASSEMBLY, WITH EMI GASKET, 2X3, ZQSFP+ STACKED	
MATERIAL: SEE NOTE 1	SEE NOTE 2	WEIGHT: -	SIZE: A100779	RESTRICTED TO: -
CUSTOMER DRAWING		SCALE: 4:1	SHEET: 1 OF 4	REV: A


LOC		DIST		REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN	APVD	
		-	-	SEE SHEET 1	-	-	-	




RECOMMENDED PANEL CUTOUT
AND PC BOARD, PANEL POSITION
SCALE 3:1




SECTION U-U




VIEW Y-Y




2227226-1/4
NO LIGHTPIPE IN ASSEMBLY
SCALE 3:1



2227226-2/5
LEFT LIGHTPIPE INDICATOR
POINTING TO UPPER PORT
SCALE 3:1




2227226-3/6
LEFT LIGHTPIPE INDICATOR
POINTING TO LOWER PORT
SCALE 3:1





SECTION V-V
SCALE 3:1


THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER: ASME Y14.5M-2009		OWN M. SHIRK CHK D. SZCZESNY APVD -	01AUG2012 01AUG2012 -	TE Connectivity	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME CAGE AND CONNECTOR ASSEMBLY, WITH EMI GASKET, 2X3, ZQSFP+ STACKED	
0 PLC 1 PLC 2 PLC 3 PLC 4 PLC ANGLES FINISH		± ±0.25 ±0.15 ± ± ± -		PRODUCT SPEC 108-60102 APPLICATION SPEC 114-60015	
MATERIAL -		WEIGHT -		SIZE A100779	
SEE NOTE 1		SEE NOTE 2		CUSTOMER DRAWING	
				SCALE 4:1 SHEET 2 OF 4 REV A	




THIS DRAWING IS A CONTROLLED DOCUMENT DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009		OWN M. SHIRK DATE 01AUG2012		TE Connectivity	
DIMENSIONS: mm		TOLERANCES, UNLESS OTHERWISE SPECIFIED:		NAME	
		0 PLOC ±.05 1 PLOC ±.25 2 PLOC ±.10 3 PLOC ±.15 4 PLOC ±. ANGLES ±. FINISH		CAGE AND CONNECTOR ASSEMBLY, WITH EMI GASKET, 2X3, ZOSFP+ STACKED	
MATERIAL		PRODUCT SPEC 108-60102		SIZE	
SEE NOTE 1		APPLICATION SPEC 114-60015		CAGE CODE	
SEE NOTE 2		WEIGHT		DRAWING NO	
		CUSTOMER DRAWING		A100779C=2272226	
				RESTRICTED TO	
				-	
				SCALE 4:1 SHEET 3 of 4 REV A	




DETAIL H
SCALE 10:1



DETAIL J
SCALE 10:1



DETAIL K
SCALE 10:1



DETAIL L
SCALE 10:1

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
-	-	SEE SHEET 1		-	-	-	-

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER: ASME Y14.5M-2009 TOLERANCES UNLESS OTHERWISE SPECIFIED:				DWN M. SHIRK CHK D. SZCZESNY APVD	01AUG2012 01AUG2012	NAME CAGE AND CONNECTOR ASSEMBLY, WITH EMI GASKET, 2X3, ZQSFP+ STACKED	
DIMENSIONS: mm		0 PLC ±.25 1 PLC ±0.15 2 PLC ±. 3 PLC ±. 4 PLC ±. ANGLES ±. FINISH		PRODUCT SPEC 108-60102 APPLICATION SPEC 114-60015		SIZE A100779C=2227226	
MATERIAL SEE NOTE 1		SEE NOTE 2		WEIGHT CUSTOMER DRAWING		RESTRICTED TO SCALE 4:1 SHEET 4 OF 4 REV A	