

## Replacement Label/Label Cover Kits

- For use with Mini-Com® Executive and Classic Series Faceplates with Labels and select Mini-Com® Surface Mount Boxes



CSGLLC-L

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
<b>Label/Label Cover Kit</b>			
CSGLLC-L	Single gang Mini-Com® Label/Label Cover Kit. Each kit contains 50 labels and 50 clear label covers.	50	250
<b>Label/Label Cover Kits with Screws</b>			
EFPK-XY	Single gang label/label cover and two screws. Also works with select surface mount boxes.	10	50
EFPK102G-XY	Double gang label/label cover and four screws.	10	50

## Low Voltage Mounting Brackets

- Choose design styles for new install or retrofit install
- Available in both single and double gang configurations



Part Number	Part Description	Std. Ctn. Qty.
LV-S-1G	Low voltage integral mounting bracket for new installations, single gang stud bracket.	25
LV-S-2G	Low voltage integral mounting bracket for new installations, double gang stud bracket.	25
LV-W-1G	Low voltage mounting bracket for retrofit installations; single gang box with screws; suitable for wall material thicknesses of 1/2" to 1 1/2".	100
LV-W-2G	Low voltage mounting bracket for retrofit installations; double gang box with screws; suitable for wall material thicknesses of 1/2" to 1 1/2".	50

## Metal Stud Grommets and Accessories

- Metal stud grommets and cable support manager support and protect cable within the building structure
- Metal Stud Punching Tool punches a 1-11/32" (34.1mm) round hole in 25 GA. min. to 20 GA max. mild steel studs; contoured handle; lightweight aluminum head; automatic hole centering on standard width (3.625") studs; replaceable punch and dies; self-stripping design that eliminates punch hang-ups




MSG-1.3-C

MSGV-1.3-C



MSPT-1.3



CSM-1.25-C

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
MSG-1.3-C	Metal stud grommet, 1-11/32" hole.	100	1000
MSGV-1.3-C	Metal stud grommet, 1-11/32" hole, anti-vibration for 1/2" to 1" pipe.	100	1000
MSPT-1.3	Metal stud punch tool with contoured handle for increased leverage.	1	0
CSM-1.25-C	Cable stud manager for 1.25" cable spacing.	100	1000