

# Product: <u>1489A</u> ☑

Inst, 24 Pr #16+22 Str BC, PVC Ins E1, OS, Blk PVC Jkt, 300V PLTC-ER ITC-ER CMG

😭 Request Sample

# **Product Description**

UL Instrumentation, 24 Pair 16+22AWG (7x24+7x30) Bare Copper, PVC Insulation E1 Color Code, Overall Beldfoil® Shield, Black PVC Outer Jacket, PLTC-ER ITC-ER CMG AWM 2464 SUN RES DIR BUR

# **Technical Specifications**

# **Product Overview**

Suitable Applications:	Industrial Control, Raceways Cable trays and ducts, Digital Control, Instruments (4-20ma, 0-10v,), low voltage digital control (24v,), encoders, control circuits, distributed control system (DCS), programmable logic controller (PLC), Solenoids, Valves, Actuators, Positioners

# **Construction Details**

#### Conductor

Element	Number of Element	AWG	Stranding	Material
Pair(s)	24	16	7x24	BC - Bare Copper
Comm Wire	1	22	7x30	BC - Bare Copper

#### Insulation

	Element	Material	Thickness [in.]	Color Code
	Pair(s)	PVC - Polyvinyl Chloride	0.017	Black, White and Numbered
ĺ	Comm Wire	PVC - Polyvinyl Chloride	0.019	Orange

#### **Outer Shield Material**

Shield Type	Material	Coverage	Drainwire Type
Таре	Alum / Poly	100%	16 AWG (7x24) TC

### Outer Jacket Material

Material	Thickness	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.074 in	1.075 in	Yes
Cable Diameter (Nominal):	1.075 in		

# **Electrical Characteristics**

#### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)
Pair(s)	3.67 Ohm/1000ft	32 pF/ft	58 pF/ft
Comm Wire	14.7 Ohm/1000ft		
Nom Outer S	Shield DCR: 2.8 Ohm/1	000ft	

#### Voltage

UL Voltage Rating 300 V (PLTC-ER, CMG, UL AWM 2464), 150 V (ITC-ER)

#### **Mechanical Characteristics**

Temperature

#### Bend Radius

Stationary Min.	Installation Min.
10.4 in	10.8 in
Max. Pull Tensio	n: 1749 lbs
ulk Cable Weigl	ht: 664 lbs/1

## **Standards and Compliance**

JL1685 (FT4 Loading), FT4, 1202				
cle 725, Article 727, Article 800, CMG, PLTC-ER, ITC-ER				
164				
MG				
J CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)				
nina RoHS II (GB/T 26572-2011)				
ticl 164 MG J C				

# **History**

Update and Revision: Revision Number: 0.350 Revision Date: 07-28-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.