



Main

Range of product	OsiSense XG
Product or component type	Portable diagnostic terminal
RFID diagnostic terminal name	XGST
Processor name	CPU ARM7

Complementary

RFID frequency	13.56 MHz
Terminal use	Diagnostics on compact stations Read / write operations on tags
[Us] rated supply voltage	5 V DC AC external adaptor 3.7 V DC internal battery
Autonomy	8 h
Memory description	Expandable USB memory stick, up to 2 GB Internal data storage Compact Flash, 2 GB Internal RAM RAM/SDRAM, 256 kB
Display type	OLED colour touchscreen
Display size	54 x 95 mm
Pixel resolution	480 x 272 pixels
Status LED	1 LED charging
Communication port support	RS485 non isolated USB
Marking	CE
Product weight	0.65 lb(US) (0.295 kg)

Environment

product certifications	CE
ambient air temperature for operation	32...113 °F (0...45 °C)
ambient air temperature for storage	-4...113 °F (-20...45 °C)
relative humidity	5...95 %
IP degree of protection	IP40

Offer Sustainability

Not Green Premium product	Not Green Premium product
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Dimensions

RFID Handheld Terminal

