9001K3L1YH13



Main

Range of product	Harmony 9001K
Product or component type	Illuminated push-button
Device short name	К
Type of operator	Spring return
Operator profile	Yellow flush
Operator additional information	Extended metallic guard

Complementary

Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Shape of signaling unit head	Round	
Light source	Incandescent	
Light source	Without	,
Bulb base	BA 9s	,
Light block supply	Via integral transformer	
[Us] rated supply voltage	110120 V AC 50/60 Hz	
Contacts type and composition	1 C/O	
Connections - terminals	Screw clamp terminals	
Operating position	Any position	
[le] rated operational current	10 A (AC-15) 10 A (DC-13)	
Contact operation	Standard	
Device presentation	Complete product	

Environment

product certifications	CE NEMA UL listed file E42259 CCN NKCR CSA LR24590 class 3211 03	dt to opitalisation
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13	4

Offer Sustainability

WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------