

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	19MAR2015	DL	CW
	B	ECR-15-013292	24SEP2015	DL	CW

M4 SCREW  
RECOMMENDED TIGHTENING TORQUE 1.2Nm

4 X M3 SCREW  
RECOMMENDED TIGHTENING TORQUE 0.5Nm

PANEL CUT OUT FOR INSERTS FOR USING  
WITHOUT HOODS/HOUSINGS

NOTES:

1. TECHNICAL CHARACTERISTICS:  
 INSULATION MATERIAL: PC  
 RATED VOLTAGE: 250 V  
 RATED CURRENT: 10 A  
 INSULATION RESISTANCE:  $\geq 400M\Omega$   
 RATED IMPULSE VOLTAGE: 2.5 KV  
 POLLUTION DEGREE: 2  
 FLAMMABILITY: UL94V-0  
 MATING CYCLES: 500 CYCLES  
 OPERATION TEMPERATURE:  $-40-+125^{\circ}C$   
 WIRE RANGE: 0.14-2.5 mm<sup>2</sup> (26-14 AWG)  
 CONTACT TYPE: ROLLED CRIMP CONTACT


2. CONTACT NEED TO BE ORDERED SEPARATELY.

注释:

1. 技术参数:  
 绝缘材料: PC  
 额定电压: 250V  
 额定电流: 10A  
 绝缘电阻:  $\geq 400M\Omega$   
 额定脉冲电压: 2.5 KV  
 污染等级: 2  
 阻燃等级: UL94V-0  
 插拔次数: 500次  
 工作温度:  $-40-+125^{\circ}C$   
 接线范围: 0.14-2.5 mm<sup>2</sup> (26-14 AWG)  
 接线类型: 卷皮式冷压接

2. 端子需要单独订购.

HDD-024-FJ	T2030243201-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	DAVID LI	18MAR2015	 TE Connectivity	NAME		HDD-024-FJ		
DIMENSIONS:		CHK	CHRIS WANG	18MAR2015		PRODUCT SPEC		108-137043		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	XU XIANG	18MAR2015		APPLICATION SPEC		114-137043		
mm						WEIGHT		-		
0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±-		MATERIAL			FINISH		-			
-		-			-		-			
-		-			-		-			
CUSTOMER DRAWING					SCALE	1:1	SHEET	1 OF 1	REV	B

1470-19 (3/13)