

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
A		INITIAL RELEASE	19MAR2015	DL	CW
B		ECR-15-013292	24SEP2015	DL	CW

M4 SCREW
RECOMMENDED TIGHTENING TORQUE 1.2Nm

4 X M3 SCREW
RECOMMENDED TIGHTENING TORQUE 0.5Nm

PANEL CUT OUT FOR INSERTS FOR USING
WITHOUT HOODS/HOUSINGS

NOTES:

1. TECHNICAL CHARACTERISTICS:
 INSULATION MATERIAL: PC
 RATED VOLTAGE: 250 V
 RATED CURRENT: 10 A
 INSULATION RESISTANCE: $\geq 400M\Omega$
 RATED IMPULSE VOLTAGE: 2.5 KV
 POLLUTION DEGREE: 2
 FLAMMABILITY: UL94V-0
 MATING CYCLES: 500 CYCLES
 OPERATION TEMPERATURE: $-40-+125^{\circ}C$
 WIRE RANGE: 0.14-2.5 mm² (26-14 AWG)
 CONTACT TYPE: ROLLED CRIMP CONTACT


2. CONTACT NEED TO BE ORDERED SEPARATELY.

注释:

1. 技术参数:
 绝缘材料: PC
 额定电压: 250V
 额定电流: 10A
 绝缘电阻: $\geq 400M\Omega$
 额定脉冲电压: 2.5 KV
 污染等级: 2
 阻燃等级: UL94V-0
 插拔次数: 500次
 工作温度: $-40-+125^{\circ}C$
 接线范围: 0.14-2.5 mm² (26-14 AWG)
 接线类型: 卷皮式冷压接

2. 端子需要单独订购.

HDD-024-FJ	T2030243201-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	DAVID LI	18MAR2015	 TE Connectivity	NAME	HDD-024-FJ					
DIMENSIONS:		CHK	CHRIS WANG	18MAR2015			PRODUCT SPEC	108-137043	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
mm		APVD	XU XIANG	18MAR2015								
TOLERANCES UNLESS OTHERWISE SPECIFIED:		MATERIAL					WEIGHT		SCALE		SHEET	
0 PLC ±-		-			-		1:1		1 OF 1		B	
1 PLC ±-		-			-		CUSTOMER DRAWING		SCALE		REV	
2 PLC ±-		-			-							
3 PLC ±-		-			-							
4 PLC ±-		-			-							
ANGLES ±-		-			-							
		-			-							

1470-19 (3/13)