


Coaxial Cable Connector 11_PC35-50-3-4/199_U

Description

Straight cable plug

Interface standards
IEC 60169-23



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	26.5 GHz

Mechanical Data

Centre contact	plugged
Outer contact	soldered
Weight	0.0057 kg

Environmental Data

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102)	-60 °C to 100 °C compliant
--	-------------------------------

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PS (Polystyrene)	
Coupling nut	Stainless Steel	
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing	DOU-00064428
Catalogue drawing	DCA-00089646
Assembly instruction	DOC-0000215467

Ordering Information

Single package	11_PC35-50-3-4/199_UE
----------------	-----------------------

Additional Information

Suitable cables	EZ_141_TP_M17, EZ_141_AL_TP_M17, SUCOFORM_141, MULTIFLEX_141
-----------------	--

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[11_PC35-50-3-4/199_UE](#)