9001K53J35G



Main

Range of product	ange of product Harmony 9001K	
Product or component type	Illuminated selector switch	
Device short name	9001K	
Type of operator	Spring return (both sides to centre)	
Operator profile	Standard knob green	

Complementary

Bezel material	Chromium plated metal	_
Mounting diameter	1.18 in (30 mm)	_
Product weight	0.54 lb(US) (0.245 kg)	_
Shape of signaling unit head	Round	_
Operator position information	3 positions	_
Contacts type and composition	Without contact block	_
Mechanical durability	500000 cycles	_
Light block supply	Direct	_
Light source	Incandescent	_
Bulb base	BA 9s	-
[Us] rated supply voltage	2428 V AC/DC	-
Device presentation	Basic element	_

Environment

protective treatment	TC	
ambient air temperature for storage	-40158 °F (-4070 °C)	
ambient air temperature for operation	-13158 °F (-2570 °C)	
electrical shock protection class	Class II conforming to IEC 61140	
IP degree of protection	IP66 conforming to IEC 60529	
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 6	
standards	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14	
product certifications	NEMA UL 508	
vibration resistance	7 gn (f = 2500 Hz) conforming to IEC 60068-2-6	
shock resistance	50 gn conforming to IEC 60068-2-27	

Offer Sustainability

WARNING: This product can expose you to chemicals WARNING: This product can expose you to chemicals including:

including:			
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.		
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov		

		e de la companya de
('ontractua	l warranty

Warranty period 18 months		
---------------------------	--	--

