


		DESIGNED FOR USE WITH RG-174/U OR EQUIVALENT		REVISIONS											
		CABLE ENTRY DIAMETER MINIMUM		REV	DESCRIPTION	DATE	APPROVED								
				010	RELEASED	06/15/94	AD								
		CONTACT .021 DIELECTRIC .021 SLEEVE .066 FERRULE .125													
<table><tr><th>ELECTRICAL</th><th>MECHANICAL</th><th>ENVIRONMENTAL</th></tr><tr><td>Nominal Impedance (Ohms) 50 Frequency Range (GHz) DC to 12.4 Volt Rating (VRMS MAX) @ Sea Level 250 VSWR 1.15 + .02 f(GHz) Insertion Loss (dB MAX) .06 √f(GHz) RF Leakage (dB MIN) -60 @ 2-3 GHz Corona, 70,000 Ft (VRMS MIN) 250 Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750 Contact Resistance (Milliohms MAX) Center Contact 3.0 Outer Contact 2.0 Cable to Housing .05 RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670 I.R.(Megohms MIN) 5,000</td><td>Interface Dimensions MIL-STD-348A, Fig. 310.1 Recommended Mating Torque 7 - 10 in-lbs Mating Characteristics: Insertion (MAX Lbs) N/A Withdrawal (MIN Oz) N/A Force to Engage and Disengage (In-Lbs MAX) 2.0 Center Contact Captivation Axial (Lbs) 6.0 Radial (In-Oz) N/A Cable Retention Axial Force (Lbs MIN) 30 Torque (In-Oz) N/A Weight (Grams) TBD</td><td>Temperature Rating -65°C to +165°C Vibration MIL-STD-202, Method 204, Condition D. Shock MIL-STD-202, Method 213, Condition I. Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp 85°C Moisture Resistance MIL-STD-202, Method 106 Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray .XXX = in XX.X = mm</td></tr></table>		ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50 Frequency Range (GHz) DC to 12.4 Volt Rating (VRMS MAX) @ Sea Level 250 VSWR 1.15 + .02 f(GHz) Insertion Loss (dB MAX) .06 √f(GHz) RF Leakage (dB MIN) -60 @ 2-3 GHz Corona, 70,000 Ft (VRMS MIN) 250 Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750 Contact Resistance (Milliohms MAX) Center Contact 3.0 Outer Contact 2.0 Cable to Housing .05 RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670 I.R.(Megohms MIN) 5,000	Interface Dimensions MIL-STD-348A, Fig. 310.1 Recommended Mating Torque 7 - 10 in-lbs Mating Characteristics: Insertion (MAX Lbs) N/A Withdrawal (MIN Oz) N/A Force to Engage and Disengage (In-Lbs MAX) 2.0 Center Contact Captivation Axial (Lbs) 6.0 Radial (In-Oz) N/A Cable Retention Axial Force (Lbs MIN) 30 Torque (In-Oz) N/A Weight (Grams) TBD	Temperature Rating -65°C to +165°C Vibration MIL-STD-202, Method 204, Condition D. Shock MIL-STD-202, Method 213, Condition I. Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp 85°C Moisture Resistance MIL-STD-202, Method 106 Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray .XXX = in XX.X = mm	<table><tr><td>HOUSING COUPLING NUT CLAMP NUT INNER SLEEVE DIELECTRIC CENTER CONTACT RETAINING RING GASKET FERRULE</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303 TFE FLUOROCARBON PER ASTM-D-1457 BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H SILICONE RUBBER PER ZZ-R-765 COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM</td><td>PASSIVATE PER ASTM-A380 N/A GOLD PLATE PER MIL-G-45204 N/A N/A GOLD PLATE PER MIL-G-45204</td></tr><tr><td>COMPONENT</td><td>MATERIAL</td><td>FINISH</td></tr></table>		HOUSING COUPLING NUT CLAMP NUT INNER SLEEVE DIELECTRIC CENTER CONTACT RETAINING RING GASKET FERRULE	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303 TFE FLUOROCARBON PER ASTM-D-1457 BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H SILICONE RUBBER PER ZZ-R-765 COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	PASSIVATE PER ASTM-A380 N/A GOLD PLATE PER MIL-G-45204 N/A N/A GOLD PLATE PER MIL-G-45204	COMPONENT	MATERIAL	FINISH
ELECTRICAL	MECHANICAL	ENVIRONMENTAL													
Nominal Impedance (Ohms) 50 Frequency Range (GHz) DC to 12.4 Volt Rating (VRMS MAX) @ Sea Level 250 VSWR 1.15 + .02 f(GHz) Insertion Loss (dB MAX) .06 √f(GHz) RF Leakage (dB MIN) -60 @ 2-3 GHz Corona, 70,000 Ft (VRMS MIN) 250 Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750 Contact Resistance (Milliohms MAX) Center Contact 3.0 Outer Contact 2.0 Cable to Housing .05 RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670 I.R.(Megohms MIN) 5,000	Interface Dimensions MIL-STD-348A, Fig. 310.1 Recommended Mating Torque 7 - 10 in-lbs Mating Characteristics: Insertion (MAX Lbs) N/A Withdrawal (MIN Oz) N/A Force to Engage and Disengage (In-Lbs MAX) 2.0 Center Contact Captivation Axial (Lbs) 6.0 Radial (In-Oz) N/A Cable Retention Axial Force (Lbs MIN) 30 Torque (In-Oz) N/A Weight (Grams) TBD	Temperature Rating -65°C to +165°C Vibration MIL-STD-202, Method 204, Condition D. Shock MIL-STD-202, Method 213, Condition I. Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp 85°C Moisture Resistance MIL-STD-202, Method 106 Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray .XXX = in XX.X = mm													
HOUSING COUPLING NUT CLAMP NUT INNER SLEEVE DIELECTRIC CENTER CONTACT RETAINING RING GASKET FERRULE	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303 TFE FLUOROCARBON PER ASTM-D-1457 BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H SILICONE RUBBER PER ZZ-R-765 COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	PASSIVATE PER ASTM-A380 N/A GOLD PLATE PER MIL-G-45204 N/A N/A GOLD PLATE PER MIL-G-45204													
COMPONENT	MATERIAL	FINISH													
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1° These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.		DRAWN BY ADAMS DATE 06/15/94 CHECKED BY APPD BY USE ASS'Y PROCEDURE 408-04904 NO. AP. (20-510)		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599 TITLE OSM STRAIGHT CABLE PLUG SOLDER CLAMP ATTACHMENT M39012/55-3007 CAT. A <table><tr><td>SIZE B</td><td>CODE IDENT NO. 26805</td><td>2031-8007-92</td><td>REV 010</td></tr><tr><td colspan="2">SCALE 6 : 1</td><td colspan="2">SHEET 1 OF 1</td></tr></table>		SIZE B	CODE IDENT NO. 26805	2031-8007-92	REV 010	SCALE 6 : 1		SHEET 1 OF 1			
SIZE B	CODE IDENT NO. 26805	2031-8007-92	REV 010												
SCALE 6 : 1		SHEET 1 OF 1													