


SPECIFICATION CONTROL DRAWING



Product Revision		Product Dimensions				Cable Dimensions				
Product Name		øA min	øB min	øC min	L max	øE		øD max	F max	M±1.00 (M±0.04)
						min	max			
B-070-12-08-01	A	7.0 (0.275)	5.3 (0.210)	5.5 (0.215)	26.5 (1.045)	2.4 (0.095)	5.5 (0.215)	7.0 (0.275)	5.3 (0.210)	12 (0.470)


MATERIALS

1. INSULATION SLEEVE: Heat-shrinkable, transparent blue, radiation cross-linked modified polyvinylidene fluoride.
2. SOLDER PREFORM WITH FLUX:
 - SOLDER: TYPE Sn96 per ANSI-J-STD-006.
 - FLUX: TYPE ROM1 per ANSI-J-STD-004.
3. SHIELD: Solder impregnated, flux coated, tin plated copper braid.
 - SOLDER: TYPE Sn96 per ANSI-J-STD-006.
 - FLUX: TYPE ROM1 per ANSI-J-STD-004.

APPLICATION

1. These controlled soldering devices are designed for shield termination of a tin, silver or nickel plated shielded cable, having an insulation rated for at least 125°C.
2. Temperature range: -55°C to +175°C.
3. Installation Procedure: RPIP-500-07.

For best results, prepare the cable as shown:



		Raychem 305 Constitution Drive Menlo Park, CA 94025, USA		TITLE : SOLDERSHIELD DEVICE			
Unless otherwise specified dimensions are in millimeters. Inches dimensions are in between brackets.				DOCUMENT NO.: B-070-12-08-01			
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ANGLES: N/A ROUGHNESS IN MICRON	Tyco Electronics reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.		DCR NUMBER: D020391		REPLACES: D010409	
PREPARED BY: mforonda		DATE: 6/14/01	PROD. REV. A	DOC ISSUE: 1	SCALE: None	SIZE: A	SHEET: 1 of 1

If this document is printed it becomes uncontrolled. Check for the latest revision.