

If this document is printed it becomes uncontrolled.
Check with the web for latest revision.

| REVISIONS | | | |
|-----------|----------------------------|---------|----------|
| LTR | DESCRIPTION | DATE | APPROVED |
| NC | RELEASED PER E.C.N. T-9695 | 88-3-8 | Z.E.T. |
| A | REVISED PER E.C.N. T-12027 | 89-4-12 | 326 |



| PART No. | CONNECTOR | CONTACT | INTERFACE |
|----------------|-----------|---------|-----------|
| DK-621-0045-3P | PLUG | PIN | C |
| DK-621-0045-3S | PLUG | SOCKET | C |
| DK-621-0046-3P | JACK | PIN | C |
| DK-621-0046-3S | JACK | SOCKET | C |
| DK-621-0047-2P | PLUG | PIN | B |
| DK-621-0047-2S | PLUG | SOCKET | B |
| DK-621-0048-2P | JACK | PIN | B |
| DK-621-0048-2S | JACK | SOCKET | B |
| DK-621-0049-1P | PLUG | PIN | A |
| DK-621-0049-1S | PLUG | SOCKET | A |
| DK-621-0050-1P | JACK | PIN | A |
| DK-621-0050-1S | JACK | SOCKET | A |
| DK-621-0051-1P | JACK | PIN | D |
| DK-621-0051-1S | JACK | SOCKET | D |
| DK-621-0052-1P | PLUG | PIN | D |
| DK-621-0052-1S | PLUG | SOCKET | D |

SPECIFICATION CONTROL DRAWING © Raychem Corporation 1987

| | | | | | | | | | |
|---|--------------------|--------|---------------------------|------------------------|---|--|-----------------|---------------------|-----|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. METRIC DIMENSIONS ARE IN BRACKETS. | DRAWN | RDL | 88-2-17 | <i>Raychem</i> | RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025 | | | | |
| | CHECKED | | | | TITLE | KITS FOR D-621-0045/0052 TRIAxIAL CONNECTORS | | | |
| | APPROVED | | | CAD NAME | 003277-1 | SIZE | CODE IDENT. NO. | DWG. NO. | REV |
| | APPROVED | Z.E.T. | 88-3-8 | THIRD ANGLE PROJECTION | | A | 06090 | DK-621-0045/0052-XX | A |
| DECIMALS .XXX ± NA [mm] .XX ± NA [mm] | WEIGHT lbs [g] | | DO NOT SCALE THIS DRAWING | | SHEET 1 OF 2 | | | | |

1.0 REFER TO THE FOLLOWING RAYCHEM SPECIFICATION CONTROL DRAWINGS (SCD) FOR INDIVIDUAL COMPONENT PERFORMANCE PARAMETERS, DIMENSIONS AND MATERIAL DETAILS:

D-621-0045/0052 CONNECTOR, TRIAXIAL, SUBMINIATURE BAYONET COUPLED. (INCLUDES STRAIN RELIEF AND BRAID TERMINATOR)

D-602-0126 CONTACT, PIN, TWISTED PAIR
 D-602-0127 CONTACT, SOCKET, TWISTED PAIR

2.0 REFER TO RAYCHEM SPECIFICATION D-6025 FOR PERFORMANCE AND QUALIFICATION REQUIREMENTS.

3.0 TERMINATION PROCEDURE: RAYCHEM ES 61222

**If this document is printed it becomes uncontrolled.
 Check with the web for latest revision.**

CAD NAME 003277-2

| | | | | | | |
|--------|-----|---------|---------------------------|--------------------------|---------------------------------|----------|
| DRAWN | RDL | 88-2-20 | SIZE A | CODE IDENT. NO. 06090 | DWG. NO. DK-621-0045/0052-XX | REV A |
| ISSUED | | | DO NOT SCALE THIS DRAWING | | SHEET 2 OF 2 | |