

Page
1 / 2

OPTIONS : INDICATOR / TTL DRIVE /SUPP.DIODES

NUMBER OF WAYS : 4
FREQUENCY RANGE : 0 - 3 GHz
IMPEDANCE : 50 Ohms

FREQUENCY (GHz)	0 - 3
V.S.W.R	<= 1.20
INSERT. LOSS	<= 0.20 dB
ISOLATION	>= 80 dB
AVER. POWER (*)	240 W

ACTUATOR	: NORMALLY OPEN
NOMINAL CURRENT AT 25° C (±10%)	: 102 mA
ACTUATOR VOLTAGE (Vcc)	: 28V (24 to 30V) / NEGATIVE COMMON
TERMINALS	: solder pins (250°C max./30 sec.)
INDICATOR RATING	: 1 W / 30 V / 100 mA
TTL INPUTS (E) - High level	: 2.2 to 5.5V / 800µA at 5V
- Low level	: 0 to 0.8V / 20µA at 0.8V

CONNECTORS	: SMA female per MIL C 39012
LIFE	: 5.000.000 cycles per position
SWITCHING TIME (nominal voltage;25° C)	: < 15 ms
CONSTRUCTION	: splashproof
WEIGHT	: < 220 g

OPERATING TEMPERATURE RANGE (°C) : -40 , +85
STORAGE TEMPERATURE RANGE (°C) : -55 , +85

(* : average power at 25° C per RF path)

This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary


4113-9212

DRAWING


General tolerance: ± 0,5 mm

R573 313420

Page
2/2




TTL input	RF continuity	Ind.
E1 = 1	IN ↔ 1	D.E
E2 = 1	IN ↔ 2	D.F
E3 = 1	IN ↔ 3	D.G
E4 = 1	IN ↔ 4	D.H




MARKING

TOP VIEW (TERMINALS)



SCHEMATIC DIAGRAM



ISSUE 22.Jan.08