


PCB terminal block - FK-MPT 0,5/ 2-ST-3,5BDNZVPE500 - 1710749

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB connector, nominal current: 4 A, rated voltage (III/2): 250 V, number of positions: 2, pitch: 3.5 mm, connection method: Push-in spring connection, color: green, contact surface: Tin



The figure shows a 10-position version of the product

Your advantages

- ✓ Time saving push-in connection, tools not required
- ✓ Defined contact force ensures that contact remains stable over the long term
- ✓ Intuitive use through colour coded actuation lever
- ✓ Potentials can be easily looped through – ideal for BUS applications
- ✓ Small component size for applications where space is at a premium



Key Commercial Data

Packing unit	500 pc
GTIN	
GTIN	4055626327600

Technical data

Dimensions

Length [l]	9.5 mm
Pitch	3.5 mm
Dimension a	3.5 mm

General

Range of articles	FK-MPT 0,5/...-ST
Number of positions	2
Connection method	Push-in spring connection
Insulating material group	IIIa
Rated voltage (III/2)	250 V
Nominal current I _N	4 A

PCB terminal block - FK-MPT 0,5/ 2-ST-3,5BDNZVPE500 - 1710749

Technical data

General

Nominal cross section	0.5 mm ²
Flammability rating according to UL 94	V0

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>