

Corrugated tube screw connection - HC-B-GCA-M20-PLRBK - 1412021

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



EVO corrugated pipe screw connection, size: M20, protection class: IP66, plastic

Product Features



Key commercial data

Packing unit	1 pc
Custom tariff number	39269097
Country of origin	Poland

Technical data

General

Assembly instructions	Please observe the installation note provided for the WP-PA HF-HB.....BK corrugated pipe
-----------------------	--

Ambient conditions

Ambient temperature (operation)	-40 °C ... 115 °C
Degree of protection	IP66

Classifications

eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27261207
eCl@ss 8.0	27449290

ETIM

ETIM 4.0	EC000441
----------	----------

Corrugated tube screw connection - HC-B-GCA-M20-PLRBK - 1412021

Classifications

ETIM

ETIM 5.0	EC000441
----------	----------

Approvals

Approvals

Approvals

EAC

Ex Approvals


Approvals submitted

Approval details

EAC

Drawings

Dimensional drawing



Dimensional drawing