






REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
S		REVISED PER ECO-17-004657	05APR2017	RS	MZ

- 1
- RECEPTACLE IS LOADED WITH 4 TYPE III+ POSTED PIN CONTACTS.
- 2
- CONTACT BODY: GOLD PER MIL-G-45204 OVER NICKEL PER QQ-N-290.
CONTACT POST: TIN-LEAD PER MIL-T-10727 OVER COPPER PER MIL-C-14550A.
- 3
- CONTACT BODY: GOLD PER MIL-G-45204 OVER NICKEL PER QQ-N-290.
CONTACT POST: TIN OVER COPPER PER MIL-C-14550A.
- 4
- CONTACT BODY: TIN OVER NICKEL PER MIL-C-14550A
CONTACT POST: TIN OVER NICKEL PER MIL-C-14550A



RECOMMENDED P.C. BOARD LAYOUT

	3	4	.220	YES	NO	1-207825-5
OBSOLETE	3	4	.429	YES	YES	1-207825-4
OBSOLETE	3	4	.119	NO	NO	1-207825-2
OBSOLETE	3	4	.618	NO	YES	1-207825-1
OBSOLETE	3	3	.119	YES	YES	1-207825-0
OBSOLETE	2	3	.119	NO	YES	207825-9
OBSOLETE	2	2	.220	YES	NO	207825-8
OBSOLETE	2	2	.429	YES	YES	207825-7
OBSOLETE	2	2	.119	NO	NO	207825-6
OBSOLETE	2	2	.119	NO	NO	207825-5
OBSOLETE	2	2	.618	NO	YES	207825-4
OBSOLETE	2	2	.119	YES	YES	207825-3
OBSOLETE	2	2	.220	NO	YES	207825-2
OBSOLETE	2	2	.119	NO	YES	207825-1

CONTACT FINISH	A	PERIPHERAL SEAL	THREADED INSERTS	PART NUMBER
----------------	---	-----------------	------------------	-------------

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R.LEE BG 7-1-91	TE Connectivity	
DIMENSIONS: INCHES		CHK W.G.LENKER 4-14-92		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD -	NAME RECEPTACLE ASSEMBLY, POSTED, STD SEX, SERIES 1, 11-4, CPC	
0 PLC ± -		PRODUCT SPEC 108-10024		
1 PLC ± -		APPLICATION SPEC -	SIZE A2	CAGE CODE 00779
2 PLC ± -		WEIGHT -	DRAWING NO C=207825	RESTRICTED TO -
3 PLC ± .005		CUSTOMER DRAWING	SCALE 2:1	SHEET 1 of 1
4 PLC ± -				REV S
ANGLES ± -				
FINISH				
CONTACT: 2				