


A.  
System  
Overview

## Stra-Strap® Cable Ties – Weather Resistant Nylon 6.6

B1.  
Cable Ties

- Greater resistance to damage caused by ultraviolet light – indoor or outdoor use
- Used for normal bundling and through-panel applications
- Small head height allows more efficient use of space in compact areas
- Exclusive two-piece design offers the lowest threading force in the industry
- Average 14% lighter than one-piece cable ties
- Releasable prior to final tensioning for bundle modifications

B2.  
Cable  
Accessories



B3.  
Stainless  
Steel Ties



C1.  
Wiring  
Duct

C2.  
Surface  
Raceway

| Part Number                       | Length |     | Width |     | Thickness |     | Max. Bundle Dia. |     | Min. Loop Tensile Str. |     | Recommended Installation Tool                          | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-----------------------------------|--------|-----|-------|-----|-----------|-----|------------------|-----|------------------------|-----|--|----------------|----------------|
|                                   | In.    | mm  | In.   | mm  | In.       | mm  | In.              | mm  | Lbs.                   | N   |  |                |                |
| <b>Miniature Cross Section</b>    |        |     |       |     |           |     |                  |     |                        |     |  |                |                |
| <b>SST1M-C0</b>                   | 4.0    | 102 | .095  | 2.4 | .035      | .9  | .78              | 20  | 18                     | 80  | GTS, GTSL, GS2B, PTS, PPTS, STS2                       | 100            | 1000           |
| <b>SST1.5M-M0</b>                 | 5.5    | 140 | .095  | 2.4 | .037      | .9  | 1.25             | 32  | 18                     | 80  |  | 1000           | 50000          |
| <b>Intermediate Cross Section</b> |        |     |       |     |           |     |                  |     |                        |     |  |                |                |
| <b>SST1.5I-M0</b>                 | 5.3    | 137 | .135  | 3.4 | .037      | .9  | 1.25             | 32  | 40                     | 178 | GTS, GTSL, GS2B, PTS, PPTS, STS2                       | 1000           | 25000          |
| <b>SST2I-M0</b>                   | 8.1    | 206 | .135  | 3.4 | .040      | 1.0 | 2.00             | 51  | 40                     | 178 |  | 1000           | 25000          |
| <b>SST3I-C0</b>                   | 11.0   | 279 | .135  | 3.4 | .040      | 1.0 | 3.00             | 76  | 40                     | 178 |  | 100            | 1000           |
| <b>SST4I-M0</b>                   | 14.7   | 375 | .135  | 3.4 | .040      | 1.0 | 4.00             | 102 | 40                     | 178 |  | 1000           | 10000          |
| <b>Standard Cross Section</b>     |        |     |       |     |           |     |                  |     |                        |     |  |                |                |
| <b>SST1.5S-M0</b>                 | 5.7    | 146 | .180  | 4.6 | .045      | 1.2 | 1.25             | 32  | 50                     | 222 | GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2 | 1000           | 25000          |
| <b>SST2S-C0</b>                   | 6.7    | 172 | .180  | 4.6 | .045      | 1.2 | 1.75             | 45  | 50                     | 222 |  | 100            | 1000           |
| <b>SST3S-C0</b>                   | 11.0   | 279 | .180  | 4.6 | .048      | 1.2 | 3.00             | 76  | 50                     | 222 |  | 100            | 1000           |
| <b>SST4S-C0</b>                   | 15.0   | 381 | .180  | 4.6 | .048      | 1.2 | 4.00             | 102 | 50                     | 222 |  | 100            | 1000           |
| <b>Light-Heavy Cross Section</b>  |        |     |       |     |           |     |                  |     |                        |     |  |                |                |
| <b>SST2H-D0</b>                   | 8.0    | 203 | .300  | 7.6 | .062      | 1.6 | 2.00             | 51  | 120                    | 534 | GTH, GS4H, GS4EH, PTH, STH2, ST3EH                     | 500            | 5000           |
| <b>SST4H-L0</b>                   | 14.8   | 376 | .300  | 7.6 | .067      | 1.7 | 4.00             | 102 | 120                    | 534 |  | 50             | 500            |
| <b>SST8H-L0</b>                   | 27.5   | 699 | .300  | 7.6 | .067      | 1.7 | 8.00             | 203 | 120                    | 534 |  | 50             | 500            |

E1.  
Labeling  
Systems

E2.  
Labels

E3.  
Pre-Printed  
& Write-On  
Markers

E4.  
Permanent  
Identification

E5.  
Lockout/  
Tagout  
& Safety  
Solutions

F.  
Index