





REV.	DATE	DESCRIPTION
A	06/24/96	ADD CONTACT PIN AND FERRULE
B	11/02/05	UPDATE DRAWING FORMAT
C	06/18/07	ADD COUPLING NUT TO PARTS LIST



RECOMMENDED CABLE
STRIPPING DIMENSIONS



					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007” .315 – 1.180 = ± 0.015” 1.180 – 4.724 = ± 0.020”	APPROVALS		DATE		Amphenol Connex									
8						DRAWN	G.R.S.	06/18/07											
7						CHECKED													
6						ISSUED													
5						SHEET	1 OF 1				PART DESCRIPTION								
4	CONTACT PIN	BRASS	GOLD	1						SMA SEMI-RIGID PLUG									
3	INSULATOR	TEFLON	NATURAL	1						PASSIVATED S.S. (FOR .141” CABLE)									
2	BODY	PASSIVATED S.S.	S.S.	1								PART NO.							
1	COUPLING NUT	PASSIVATED S.S.	S.S.	1								132200							
	DESCRIPTION	MATERIAL	FINISH	QTY		DO NOT SCALE DRAWING		CAD FILE		C:/132/132200.DWG		DWG. NO.		132200.DWG		REV.	C	SIZE	A