


LOC	DIST	REVISIONS					
—	—	P	LTR	DESCRIPTION	DATE	DWN	APVD
			7	ECR-12-015027	24AUG2012	HD	CD

a) Part as supplied



b) Part fully recovered



PRODUCT DIMENSIONS & NOTES

DIMENSIONS (in millimetres)

D DIA.	d DIA.	W
	MAX	±0.20
a	b	b
9.5 – 12.0	1.5	1.6

NOTES:

Material conforms to RAYCHEM specification RK-6214.
 Longitudinal shrinkage on full recovery = -5 to -15%
 Supplied wall thickness concentricity = 60% minimum.

MATERIAL: 1. JACKET Irradiated Modified Polyolefin. (Colour: Clear)
 2. LINER Hot melt adhesive. (Colour: Light Amber)

RELEASED FOR PUBLICATION AUG , 2012.

ALL RIGHTS RESERVED.

© COPYRIGHT 2011 Tyco Electronics UK Ltd, Swindon, UK

THIS DRAWING IS UNPUBLISHED.

DIMENSIONS: mm	DWN	31JUL2002	MATERIAL	—	FINISH	—
	AL					
TOLERANCES UNLESS OTHERWISE SPECIFIED:	CHK	—	TE Connectivity			
	APVD	30JUL2002				
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -	CD		NAME			
	PRODUCT SPEC	RK-6214	RPPM-NR510			
	APPLICATION SPEC	—	SIZE	A4	CAGE CODE	—
	WEIGHT	12.99g/m	DRAWING NO	RPPM-NR510		RESTRICTED TO
	CUSTOMER DRAWING		SCALE	1:1	SHEET	1 OF 1
						REV 7