

0337	4280	5280	0332
<p>0337-0-XX-XX-15-XX-10-0 Solder mount in $\text{Ø}0.066 \pm 0.003$ PTH. #15 Contact for $\text{Ø}0.020$-.032 pins. Also available on 8mm wide carrier tape: 6,000 parts per 13" reel.</p>	<p>4280-0-XX-XX-16-XX-10-0 Solder mount in $\text{Ø}0.067 \pm 0.003$ PTH. #16 Contact for $\text{Ø}0.022$-.034 pins. Also available on 8mm wide carrier tape: 6,000 parts per 13" reel.</p>	<p>5280-0-XX-XX-16-XX-40-0 Solder mount in $\text{Ø}0.067 \pm 0.003$ PTH. #16 Contact for $\text{Ø}0.022$-.034 pins. Also available on 16mm wide carrier tape: 2,200 parts per 13" reel.</p>	<p>0332-0-XX-XX-18-XX-10-0 Solder mount in $\text{Ø}0.079 \pm 0.003$ PTH. #18 Contact for $\text{Ø}0.037$-.043 pins. Also available on 16mm wide carrier tape: 2,200 parts per 13" reel.</p>
0479	0375	0353	0384
<p>0479-0-XX-XX-34-XX-10-0 Solder mount in $\text{Ø}0.077 \pm 0.003$ PTH. #34 Contact for $\text{Ø}0.032$-.046 pins. Also available on 16mm wide carrier tape: 2,000 parts per 13" reel.</p>	<p>0375-0-XX-XX-02-XX-10-0 Solder mount in $\text{Ø}0.087 \pm 0.003$ PTH. #02 Contact for $\text{Ø}0.040$-.050 pins. Also available on 12mm wide carrier tape: 4,500 parts per 13" reel.</p>	<p>0353-0-XX-XX-03-XX-10-0 Solder mount in $\text{Ø}0.106 \pm 0.003$ PTH. #03 Contact for $\text{Ø}0.040$-.060 pins. Also available on 12mm wide carrier tape: 1,300 parts per 13" reel.</p>	<p>0384-0-XX-XX-23-XX-10-0 Solder mount in $\text{Ø}0.105 \pm 0.003$ PTH. #23 Contact for $\text{Ø}0.045$-.065 pins. Also available on 12mm wide carrier tape: 2,000 parts per 13" reel.</p>
0376	0321	3435	
<p>0376-0-XX-XX-07-XX-10-0 Solder mount in $\text{Ø}0.133 \pm 0.003$ PTH. #07 Contact for $\text{Ø}0.065$-.082 pins. Also available on 16mm wide carrier tape: 1,500 parts per 13" reel.</p>	<p>0321-0-XX-XX-08-XX-10-0 Solder mount in $\text{Ø}0.144 \pm 0.003$ PTH. #08 Contact for $\text{Ø}0.084$-.102 pins. Also available on 16mm wide carrier tape: 1,700 parts per 13" reel.</p>	<p>3435-0-XX-XX-47-XX-04-0 Solder mount in $\text{Ø}0.046 \pm 0.003$ PTH. #47 Contact for $\text{Ø}0.025$-.036 and .025" square pins.</p>	
<p>SPECIFICATIONS SHELL MATERIAL: Brass Alloy 360, 1/2 Hard CONTACT MATERIAL: Beryllium Copper Alloy 172, HT SOLDER BARRIER: Organic Fibre Plug® DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ± 0.005 DIAMETERS: ± 0.002 ANGLES: $\pm 2^\circ$</p>		<p>ORDER CODE: XXXX - 0 - XX - XX - XX - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY PACKAGING: →</p> <p>43 Discrete Receptacles 67 Supplied on 13" Reels</p> <p>SPECIFY SHELL FINISH: →</p> <p>01 200μm TIN/LEAD OVER NICKEL ◇ 80 200μm TIN OVER NICKEL (RoHS)</p> <p style="text-align: center;">CONTACT</p> <p>#02, #07, #08, #15, #16, #18, #23, #34 or #47 CONTACT (DATA ON PAGES 220 - 228)</p>	
<p>RoHS 2002/95/EC</p>		<p>RoHS 2002/95/EC</p>	