## www.wihatools.com



## Wiha Soft Grip Pliers & Cutters





326 High Leverage Cutters DIN ISO 5749

Low wear lap joint, riveted and able to withstand high levels of load. Low force cutting action, clean cutting. Long life edge is achieved through additional induction hardening to approx. 64HRC. Special C70 tool steel hardened and tempered. For soft & medium hard wire. Soft vinyl grips.

Item		$\leftrightarrow$	Cutting Capacity		<b>••</b>
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32638	140	5.5	#6	1	.33
32642	160	6.3	#6	1	.49
32639	180	7.0	#6	1	.54





Semi-circular. Low wear lap joint, riveted and able to withstand high

No.	mm	Inch	Copper AWG	Pkg.	lbs.	
32646	160	6.3	#6	1	.42	
32649	180	7.0	#5	1	.50	
32652	200	8.0	#4	1	.63	

**326 Cable Cutters** Light, energy-saving & clean cutting with specially ground precision cutting edges. Long life is achieved through additional induction hardening of cutting edge to 64HRC. C70 special tool steel hardened and tempered. Soft vinyl grips. For cutting of copper & aluminum cables without crushing, also suitable for stripping. Not for steel cable, wires and copper conductors with hard coatings.

	,				0
Item	$\leftrightarrow$		Cutting Capacity		<b>↓</b> •
No.	mm	Inch	Copper/Aluminum	Pkg.	lbs.
32600	160	6.3	16mm	1	.34
32602	200	7.9	20mm	1	.62

326Flush Cutting Diagonal Cutters With Return Spring ForCutting Plastic DIN ISO 5749Low wear lap joint, riveted and ableto withstand high levels of load. Lightweight action, clean cutting. Longlife edge is achieved through additional induction hardening to approx.64HRC. Special C70 tool steel hardened and tempered. For cuttingplastic tie wraps & injection mold components. Soft vinyl grips.

Item	-	► ←►		•••	
No.	mm	Inch	Pkg.	lbs.	
32607	127	5.0	1	.14	
32614	160	6.3	1	.36	



## 326 Crimping Pliers DIN ISO 5743

Semi-circular profiles for secure connection between end sleeve and conductor. Long life is achieved through additional induction hardening to 64HRC. C70 special tool steel hardened & tempered. Soft vinyl grips.

Item		$\leftrightarrow$				• <b>`</b> •
No.	mm	Inch	mm2	AWG	Pkg.	lbs.
32604	145	5.75	0.25-2.5	14-32	1	.29
32605	180	7.0	0.25-16	6-32	1	.57



