9001KP35LGG6



Main

	Range of product	Harmony 9001K	
	Product or component type	Pilot light	
	Device short name	9001K	

Complementary

Chromium plated metal
1.18 in (30 mm)
Round
Domed (glass)
Green
Green LED
BA 9s
Direct
Screw clamp terminals (1 x 0.222 x 1.5 mm²) conforming to IEC 60947-1
7.08 lbf.in (0.8 N.m) conforming to IEC 60947-1
Cross slotted
Any position
250 V (degree of pollution: 2) conforming to IEC 60947-1
2.5 kV conforming to IEC 60947-1
10 A cartridge fuse conforming to IEC 60947-5-1
10 A
2.13 in (54 mm)
2.76 in (70 mm)
1.65 in (42 mm)
2428 V AC/DC
0.3 lb(US) (0.134 kg)
Complete product

Environment

standards	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14	
product certifications	NEMA UL 508	
protective treatment	TC	
ambient air temperature for storage	-40158 °F (-4070 °C)	
ambient air temperature for operation	-13158 °F (-2570 °C)	
vibration resistance	7 gn (f = 2500 Hz) conforming to IEC 60068-2-6	
shock resistance	50 gn conforming to IEC 60068-2-27	
overvoltage category	Class II conforming to IEC 61140	

IP degree of protection	IP66 conforming to IEC 60529
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3R
	NEMA 4 NEMA 6

Offer Sustainability

Warranty period

WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov
Contractual warranty	

18 months

