

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By - ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	V	REVISED PER ECO-15-011608	04NOV2015	NK	MZ
	W	REVISED PER ECO-18-000435	17JAN2018	RS	MZ

A	[.46]	[.028]	--	12	9.5	[.375]	6	38	0.18	[.007]	04121	5-192043-0	
A	[.46]	[.028]	--	12	9.5	[.375]	1-2	38	0.18	[.007]	04128	4-192043-9	OBSOLETE
A	[.46]	[.028]	--	12	9.5	[.375]	UNPL	38	0.18	[.007]	04120	4-192043-8	OBSOLETE
A	[.55]	[.024]	--	12	9.5	[.375]	6	38	0.15	[.006]	04108	4-192043-7	19
A	[.60]	[.028]	--	12	9.5	[.375]	3-2	39	0.15	{.006}	--	4-192043-6	
A	[.55]	[.024]	--	12	9.5	[.375]	3-2	38	0.15	[.006]	04053	4-192043-5	
A	[.53]	[.024]	--	12	9.5	[.375]	1-2	38	0.15	[.006]	04067	4-192043-4	OBSOLETE
A	--	--	--	12	9.5	[.375]	1-2	38	0.15	[.006]	04092	4-192043-3	OBSOLETE
SUPERSEDED BY 4-192043-1											04107	4-192043-2	
A	[.55]	[.024]	--	12	9.5	[.375]	UNPL	38	0.15	[.006]	04071	4-192043-1	OBSOLETE
A	[.55]	[.026]	--	12	9.5	[.375]	5-2	38	0.12	[.005]	--	4-192043-0	
A	[.55]	[.026]	--	13	9.5	[.375]	1-2	38	0.12	[.005]	04174	3-192043-9	19
A	[.55]	[.026]	--	13	9.5	[.375]	UNPL	38	0.12	[.005]	--	3-192043-8	
A	[.54]	[.026]	--	12	9.1	[.359]	3-2	36	0.18	[.007]	04204	3-192043-7	OBSOLETE
A	[.54]	[.026]	--	12	9.1	[.359]	1-2	36	0.18	[.007]	04184	3-192043-6	OBSOLETE
A	[.54]	[.026]	--	12	9.1	[.359]	UNPL	36	0.18	[.007]	04183	3-192043-5	19
A	--	--	--	12	8.9	[.359]	3-2	35	0.15	[.006]	04178	3-192043-4	OBSOLETE
A	--	--	--	12	8	[.315]	3-2	30	0.18	[.007]	04177	3-192043-3	OBSOLETE
A	--	[.026]	--	12	8	[.315]	3-2	29	0.18	[.007]	04179	3-192043-2	OBSOLETE
A	[.38]	[.026]	--	12	8	[.315]	1-2	29	0.18	[.007]	04206	3-192043-1	
A	[.38]	[.026]	--	12	8	[.315]	UNPL	29	0.18	[.007]	04185	3-192043-0	OBSOLETE
A	[.43]	[.024]	--	12	8	[.315]	3-2	32	0.15	[.006]	--	2-192043-9	19
A	[.40]	[.024]	--	12	8	[.315]	1-2	31	0.15	[.006]	--	2-192043-8	
A	[.43]	[.024]	--	12	8	[.315]	1-2	32	0.15	[.006]	04076	2-192043-7	OBSOLETE
A	[.43]	[.024]	--	12	8	[.315]	UNPL	32	0.15	[.006]	04052	2-192043-6	OBSOLETE
A	[.40]	[.026]	--	13	7.9	[.312]	UNPL	32	0.12	[.005]	04079	2-192043-5	OBSOLETE 19
A	--	--	--	12	7.5	[.296]	1-2	32	0.18	[.007]	04189	2-192043-4	OBSOLETE
A	--	--	--	12	7.49	[.295]	3-2	30	0.15	[.006]	04051	2-192043-3	OBSOLETE
A	--	--	--	12	7.44	[.293]	3-2	29	0.12	[.005]	04050	2-192043-2	OBSOLETE
A	--	--	--	12	7.14	[.281]	3-2	28	0.20	[.008]	04049	2-192043-1	OBSOLETE
A	[.45]	[.024]	--	12	7.1	[.280]	3-2	28	0.15	[.006]	04106	2-192043-0	
A	[.45]	[.024]	--	12	7.1	[.280]	UNPL	28	0.15	[.006]	04199	1-192043-9	OBSOLETE 19
A	--	--	--	12	7	[.276]	3-2	27	0.12	[.005]	04047	1-192043-8	OBSOLETE
A	--	--	--	12	6.45	[.254]	7-2	26	0.15	[.006]	04065	1-192043-7	OBSOLETE
A	[.35]	[.024]	--	12	6.45	[.254]	3-2	26	0.15	[.006]	04075	1-192043-6	
A	[.35]	[.024]	--	12	6.45	[.254]	1-2	26	0.15	[.006]	04086	1-192043-5	OBSOLETE
A	[.35]	[.024]	--	12	6.45	[.254]	UNPL	26	0.15	[.006]	04046	1-192043-4	OBSOLETE 15
A	[.50]	[.026]	--	13	6.45	[.254]	UNPL	26	0.12	[.005]	04093	1-192043-3	OBSOLETE
A	[.29]	[.024]	--	12	6.35	[.250]	3-2	26	0.20	[.008]	04045	1-192043-2	19
A	[.29]	[.024]	--	12	6.35	[.250]	1-2	26	0.20	[.008]	04116	1-192043-1	
SUPERSEDED BY 1-192043-6											--	1-192043-0	
A	[.29]	[.016]	--	13	6.35	[.250]	UNPL	26	0.12	[.005]	04082	192043-9	OBSOLETE
A	[.28]	[.024]	--	12	6	[.237]	3-2	24	0.15	[.006]	04041	192043-8	
A	[.28]	[.024]	--	12	6	[.237]	UNPL	24	0.15	[.006]	04042	192043-7	19
A	[.28]	[.024]	--	12	5.54	[.218]	1-2	23	0.15	[.006]	04146	192043-6	OBSOLETE
A	[.28]	[.024]	--	12	5.54	[.218]	UNPL	23	0.15	[.006]	04143	192043-5	OBSOLETE 19
A	--	--	--	12	5.5	[.217]	3-2	21	0.20	[.008]	04040	192043-4	OBSOLETE
A	[.27]	[.024]	--	12	5.5	[.217]	3-2	21	0.15	[.006]	04105	192043-3	OBSOLETE
A	[.26]	[.024]	--	12	5	[.197]	3-2	20	0.15	[.006]	04215	192043-2	
A	[.26]	[.024]	--	12	5	[.197]	UNPL	20	0.15	[.006]	04216	192043-1	19
STYLE	(FREE DIA)	LH	LENGTH	MAT'L (NOTE)	MATING PIN Ø	REF	PLATING (NOTE NO.)	NUM LOUV	MAT'L THK	REF	PART NUMBER		

STYLE A

(FEMALE)

8.1

[.32]

(FREE DIA)

LENGTH MIN

(LOUVER HEIGHT)

8.1

[.32]

LH

STYLE A

(FEMALE)

STYLE C

(STRIP)

1 FINISH-SILVER PLATE 200 uINCH THICK MIN.

2 FINISH-NICKEL PLATE 40 uINCH THICK MIN.

3 FINISH-GOLD PLATE 10 uINCH THICK MIN.

4 FINISH

5 FINISH-GOLD PLATE 40 uINCH THICK MIN.

6 FINISH-TIN PLATE 300 uINCH THICK MIN.

7 FINISH-GOLD PLATE 50 uINCH THICK MIN.

8 FINISH-NICKEL PLATE 100 uINCH THICK MIN.

9 FINISH-PREPLATE

10

11 PLATING NOTES ARE TO BE INTERPRETED AS FOLLOWS, 6-8 AS 6 OVER 8.

12 MATERIAL-CDA172, BeCu.

13 MATERIAL-STAINLESS STEEL

14 PRODUCT IS SOLD BY THE FOOT.

15 OBSOLETE (PENDING).

16 MATERIAL: ELGILOY.

17 PRELIMINARY PART NUMBER.

18 FINISH: COPPER PLATE 10 uINCH THICK MIN.

19 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm[INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± -

2 PLC ± 0.5 [.02]

3 PLC ± 0.25 [.010]

4 PLC ± -

ANGLES ± -

FINISH

SEE TABLE

DWN RA JAYNE 09-21-91

CHK J.TURNER 07-21-93

APVD -

PRODUCT SPEC -

APPLICATION SPEC -

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

NAME CONTACT BAND, FEMALE

SIZE A2

CAGE CODE 00779

DRAWING NO C=192043

RESTRICTED TO -

SCALE 1:1

SHEET 1 of 2

REV W

192043

B

A

1471-9 (1/15)

