

Protect It! 1-Outlet Surge Protector, Direct Plug-In, 1080 Joules, 2.4A USB Charger

MODEL NUMBER: SK10USB



Highlights

- 1 outlets/direct plug-in
- 1080 joule rating
- 2.4 amp USB charging
- Diagnostic LED
- \$5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Package Includes

- SK10USB surge suppressor

Description

The SK10USB surge suppressor offers reliable surge and line noise protection. The compact direct plug-in design allows for easy portability and features 1 outlets and 1080 joules of surge energy absorption. Diagnostic LED alerts you to potential wiring or protection faults before connected equipment is damaged. 2 USB ports with 2.4 amp total USB charging offer fast charging for smartphones, tablets, MP3 players and other portable devices. \$5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- 1 outlets / direct plug-in
- Surge suppression rating: 1080 joules
- 2.4 amp USB Charger
- EMI/RFI noise filtering
- Diagnostic LED indicates Protected (green)
- \$5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Specifications

| OUTPUT | |
|-------------------------|------------|
| Charging Ports / Amps | (2) 2.4A |
| Frequency Compatibility | 60 Hz |
| Output Receptacles | (1) 5-15R |
| Output (Watts) | 1800 |
| Circuit Breaker (amps) | 15 |
| Outlet Type | NEMA 5-15P |



| INPUT | |
|------------------------------------|--|
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V |
| Input Connection Type | NEMA 5-15P input plug |
| Input Plug Features | 120V, 15A |
| Input Cord Length (ft.) | 0 |
| Input Cord Length (m) | 0.00 |
| Input Cord Length Details | Direct Plug-In |
| Voltage Compatibility (VAC) | 120 |
| SURGE / NOISE SUPPRESSION | |
| AC Suppression Joule Rating | 1080 |
| AC Suppression Response Time | < 1ns |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| Clamping Voltage (RMS) | 400,400,500 |
| UL1449 Let Through Rating | 500, 400, 500 |
| Immunity | Conforms to IEE 587/ANSI C62.41 |
| DATALINE SURGE SUPPRESSION | |
| Telephone/DSL Protection | No |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| PHYSICAL | |
| Unit Dimensions (hwd / in.) | 3.13 x 2.68 x 1.28 |
| Unit Dimensions (hwd / cm) | 7.95 x 6.81 x 3.25 |
| Material of Construction | Plastic |
| Integrated Keyhole Mounting Tabs | Direct plug-in suppressor mounts directly to a wall receptacle |
| Housing Color | Black |
| Receptacle Color | Black |
| Metal Case | No |
| SPECIAL FEATURES | |
| Right-Angle Plug | No |
| CERTIFICATIONS | |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|--|---|
| UL1449 3rd Edition (AC Suppression) | UL1449 3rd Edition |
| Approvals | RoHS |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$5,000 Ultimate Lifetime Insurance |

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>