

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	26Feb2015	GY	CW

4XM3 THREAD

2XM6 NUT

4XØ6.5

58

39

32

27

77

103

146.2

166

52.2

NOTES:

1. TECHNICAL CHARACTERISTICS:
 HOUSING MATERIAL: DIE CAST ALUMINIUM ALLOY
 SURFACE TREATMENT: SEE TABLE
 OPERATION TEMPERATURE: -40°C~+125°C
 DEGREE OF PROTECTION: IP68 (MATED)

注释

1. 技术参数:

壳体材料: 铝合金

表面处理: 见表格

工作温度: -40°C~+125°C

防护等级: IP68 (配合)

120.1

29

20

STE

IP68

STE

IP68

T1930162000-000	POWDER COATED GRAY RAL7037	H16BPR-AG
T1930161000-000	POWDER COATED SILVERGRAY RAL 7001	H16BPR-AG
T1930160000-000	POWDER COATED BLACK RAL9005	H16BPR-AG
PART NUMBER	SURFACE TREATMENT	DESCRIPTION

103

82

35

32

Panel Cut Out

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Gino.Yao 13Dec2014	 TE Connectivity			
DIMENSIONS: mm		CHK Chris.Wang 13Dec2014				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD Xiang.Xu 13Dec2014				
0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ±		NAME H16BPR-AG				
MATERIAL		PRODUCT SPEC 108-137014	SIZE A3	CAGE CODE -	DRAWING NO C-T193016X000000	RESTRICTED TO -
FINISH		APPLICATION SPEC 114-137014	SCALE 1:1		SHEET 1 OF 1	REV A
-		WEIGHT -	Customer Drawing			

1470-19 (3/13)