

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	26Feb2015	GY	CW

4XM3 THREAD

2XM6 NUT

4XØ6.5

58

39

32

27

77

103

146.2

166

52.2

NOTES:

1. TECHNICAL CHARACTERISTICS:
 HOUSING MATERIAL: DIE CAST ALUMINIUM ALLOY
 SURFACE TREATMENT: SEE TABLE
 OPERATION TEMPERATURE: -40°C~+125°C
 DEGREE OF PROTECTION: IP68 (MATED)

注释

1. 技术参数:
 壳体材料: 铝合金
 表面处理: 见表格
 工作温度: -40°C~+125°C
 防护等级: IP68 (配合)

120.1

29

20

STE

IP68

STE

IP68

103

82

35

32

Panel Cut Out

T1930162000-000	POWDER COATED GRAY RAL7037	H16BPR-AG
T1930161000-000	POWDER COATED SILVERGRAY RAL 7001	H16BPR-AG
T1930160000-000	POWDER COATED BLACK RAL9005	H16BPR-AG
PART NUMBER	SURFACE TREATMENT	DESCRIPTION

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN		Gino.Yao		13Dec2014	
mm		0 PLC	±	CHK		Chris.Wang		13Dec2014	
		1 PLC	±	APVD		Xiang.Xu		13Dec2014	
		2 PLC	±	PRODUCT SPEC		108-137014		NAME	
		3 PLC	±	APPLICATION SPEC		114-137014		H16BPR-AG	
		4 PLC	±	WEIGHT		-		SIZE	
		ANGLES	±	Customer Drawing		-		CAGE CODE	
		FINISH	-	SCALE		1:1		DRAWING NO	
			-	SHEET		1 OF 1		RESTRICTED TO	
			-	REV		A		C-T193016X000000	

1470-19 (3/13)