



- 1 CONTACTS: 0.00076[.000030] MINIMUM GOLD IN CONTACT AREA, 0.00381[.000150] MIN TIN ON SOLDER TAILS, ALL OVER 0.00127[.000050] MINIMUM NICKEL
- 2. CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM
- 3 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
- 4. CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD
- 5 ASSEMBLY KEYED FOR 5 VOLT CARDS
- 6 ASSEMBLY KEYED FOR LOW VOLT CARDS (3.3V)
- 7 RECESSED AMP AND CSA LOGOS LOCATED ON BOTH SIDES OF HOUSING.
- 8 MATERIAL: HOUSING & ORGANIZER; LCP, COLOR; BLACK CONTACTS; BRASS

6	1,17,34	ALL	36,67	5535653-2
	35,51,68	OTHER PINS		
5	1,17,34	ALL		5535653-1
	35,51,68	OTHER PINS		
VOLTAGE KEYING & IDENTIFICATION	5.0	4.25	3.5	PART NUMBER
	[.197]	[.167]	[.138]	
	"L" (PIN LENGTH) AND LOCATION			

THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN	03-23-05	NAME	PIN HEADER ASSY, 68 POSN, TOP BOARD MTG, THRU-HOLE, AMP MEMORY CARD
		L. VARELA - DOCKS	03-23-05		
DIMENSIONS: mm(INCHES)		CHK	03-23-05	PRODUCT SPEC	SIZE
		D.L. GORENC		APPLICATION SPEC	CAGE CODE
		APVD	03-23-05	WEIGHT	DRAWING NO
		M. WALMSLEY		7.3 GRAMS	00779
TOLERANCES UNLESS OTHERWISE SPECIFIED:				SCALE	REV
0 PLC	±			4:1	1
1 PLC	±				1
2 PLC	±				1
3 PLC	± 0.13 [005]				P
4 PLC	±				
ANGLES	±				
MATERIAL	FINISH				
8	1				
CUSTOMER DRAWING					

**COPYRIGHT 2005  
TE CONNECTIVITY CORP  
ALL RIGHTS RESERVED**