

THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION	- , - .
© COPYRIGHT - By -	ALL RIGHTS RESERVED.	

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
H	—		A	INITIAL RELEASE	02DEC2013	YC	BvH
			A1	ECR-14-015049	13OCT2014	GSK	BvH

NOTES:


Tolerances cable lengths:

0m to 0.5m +30mm

0.5m to 1.0m +50mm

1.0m to 3.0m +100mm


< 3.0m +1.5%



TECHNICAL DATA	
Operating voltage	24 V DC $\pm$ 25 %
Operating current per contact	max. 4 A
Locking of ports	Screw thread M12 x 1 mm (recommended torque 0.6 Nm) self-securing
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)

PUR/PVC CABLE	
No./diameter of wires	5 x 0.34 mm ²
Wire isolation	PVC (br, wh, bl, bk, gnye)
C-track properties	2 million
Jacket	PUR/PVC
Outer diameter	approx. 5.9 mm
Bend radius (moving)	15 x outer diameter
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-5...+80 °C

CABLE	
No./diameter of wires	5 x 0.34 mm ²
Wire isolation	PP (br, wh, bl, bk, gnye)
C-track properties	10 million
Jacket	PUR (UL/CSA), welding spark res.
Outer diameter	approx. 5.0 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	-40...+90 °C
Temperature range (mobile)	-25...+90 °C



5	pos	2.0mtr	SPARK RESISTANT	Black	3-2273127-5	5x22AWG SPARK RES 2.0m	20
		1.5mtr			3-2273127-4	5x22AWG SPARK RES 1.5m	19
		1.0mtr			3-2273127-3	5x22AWG SPARK RES 1.0m	18
		0.6mtr			3-2273127-2	5x22AWG SPARK RES 0.6m	17
		0.3mtr			3-2273127-1	5x22AWG SPARK RES 0.3m	16
		5			pos	2.0mtr	PUR/PVC
1.5mtr	2-2273127-4		5x22AWG PUR/PVC 1.5m	14			
1.0mtr	2-2273127-3		5x22AWG PUR/PVC 1.0m	13			
0.6mtr	2-2273127-2		5x22AWG PUR/PVC 0.6m	12			
0.3mtr	2-2273127-1		5x22AWG PUR/PVC 0.3m	11			
LENGTH "L"			MATERIAL	JACKET COLOR		TE PN	

TECHNICAL DATA	
Operating voltage	24 V DC ±25 %
Operating current per contact	max. 4 A
Locking of ports	Screw thread M12 x 1 mm (recommended torque 0.6 Nm) self-securing
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)

PUR CABLE	
No./diameter of wires	5 x 0.34 mm ²
Wire isolation	PP (br, wh, bl, bk, gnye)
C-track properties	5 million
Jacket	PUR (UL/CSA)
Outer diameter	approx. 5.0 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	-40...+80 °C
Temperature range (mobile)	-25...+80 °C

PVC CABLE	
No./diameter of wires	5 x 0.34 mm ²
Wire isolation	PVC (br, wh, bl, bk, gnye)
C-track properties	
Jacket	PVC (UL/CSA)
Outer diameter	approx. 5.2 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-5...+80 °C

5	pos	2.0mtr	PVC	Black	1-2273127-5	5x22AWG PVC 2.0m	10
		1.5mtr			1-2273127-4	5x22AWG PVC 1.5m	9
		1.0mtr			1-2273127-3	5x22AWG PVC 1.0m	8
		0.6mtr			1-2273127-2	5x22AWG PVC 0.6m	7
		0.3mtr			1-2273127-1	5x22AWG PVC 0.3m	6
		5			pos	2.0mtr	PUR
1.5mtr	2273127-4		5x22AWG PUR 1.5m	4			
1.0mtr	2273127-3		5x22AWG PUR 1.0m	3			
0.6mtr	2273127-2		5x22AWG PUR 0.6m	2			
0.3mtr	2273127-1		5x22AWG PUR 0.3m	1			
LENGTH"L"			MATERIAL	JACKET COLOR		TE PN	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN YATHISH.C 02DEC2013		 TE Connectivity							
		CHK B.VELDHOFEN 02DEC2013									
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME M12 ANGLD SCKT TO M12 STRGHT PLG 3 LED							
mm											
		0 PLC ± -									
		1 PLC ± -									
		2 PLC ± -									
		3 PLC ± -									
		4 PLC ± -									
ANGLES ± -											
MATERIAL		FINISH		SIZE		CAGE CODE		DRAWING NO		RESTRICTED TO	
-		-		A2		00779		G-2273127		-	
CUSTOMER DRAWING								SCALE		SHEET	
								NTS		1 of 1	
										REV A1	